

U-POL™

SAFETY DATA SHEET

UP0741V ACID #8 AEROSOL MIR COMPLIANT

Page 1

Issued: 21/03/2005

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: UP0741V ACID #8 AEROSOL MIR COMPLIANT

Product code: ACIDV/AL

Use / description of product: 1K ETCH PRIMER PAINT PRODUCT CONTAINING MIXTURE OF SOLVENTS

Company name: U-Pol Products

US ADDRESS:

Sanders and Associates Inc.,

1263 Route 31 South

Lebanon

NJ 08833

USA

Fax: 1-800-787-5150

Emergency tel: 1-800-424-9300 (CHEMTREC)

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ETHYL METHYL KETONE 10-30%

EINECS: 201-159-0 CAS: 78-93-3

[F] R11; [Xi] R36; [Xi] R66; [-] R67

- DIMETHYL ETHER 30-50%

EINECS: 204-065-8 CAS: 115-10-6

[F+] R12

- 1-METHOXY-2-PROPANOL 1-10%

EINECS: 203-539-1 CAS: 107-98-2

[-] R10

- BUTAN-1-OL 1-10%

EINECS: 200-751-6 CAS: 71-36-3

[-] R10; [Xn] R22; [Xi] R37/38; [Xi] R41; [-] R67

- XYLENE <1%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

- TERT-BUTYL ACETATE 10-30%

EINECS: 208-760-7 CAS: 540-88-5

[F] R11; [Xi] R66

[cont...]

SAFETY DATA SHEET

UP0741V ACID #8 AEROSOL MIR COMPLIANT

- ISOBUTANOL <1%
EINECS: 201-148-0 CAS: 78-83-1
[-] R10; [Xi] R37/38; [Xi] R41; [-] R67

3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: ETHYL METHYL KETONE

TWA (8 hr exposure limit): 600 mg/m³ STEL (15 min exposure limit): 899 mg/m³ (OES)

- DIMETHYL ETHER

TWA (8 hr exposure limit): 766 mg/m³ STEL (15 min exposure limit): 958 mg/m³ (OES)

- 1-METHOXY-2-PROPANOL

TWA (8 hr exposure limit): 375 mg/m³ STEL (15 min exposure limit): 560 mg/m³ (OES)

- BUTAN-1-OL

STEL (15 min exposure limit): 154 mg/m³ (OES)

- XYLENE

TWA (8 hr exposure limit): 220 mg/m³ STEL (15 min exposure limit): 441 mg/m³ (OES)

- TERT-BUTYL ACETATE

TWA (8 hr exposure limit): 966 mg/m³ STEL (15 min exposure limit): 1210 mg/m³ (OES)

- ISOBUTANOL

TWA (8 hr exposure limit): 154 mg/m³ STEL (15 min exposure limit): 231 mg/m³ (OES)

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Nitrile gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing with elasticated cuffs and closed neck.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Colour: Pale grey

Odour: Characteristic odour

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

SAFETY DATA SHEET

UP0741V ACID #8 AEROSOL MIR COMPLIANT

Flash point°C: -40

Relative density: 0.75

VOC g/l: 709

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

- Hazardous ingredients:** 1-METHOXY-2-PROPANOL
 IVN RAT LD50 4200 mg/kg
 ORL MUS LD50 11700 mg/kg
 ORL RAT LDLO 3739 mg/kg
- BUTAN-1-OL
 IVN RAT LD50 310 mg/kg
 ORL MUS LD50 2680 mg/kg
 ORL RAT LD50 790 mg/kg
 - XYLENE
 ORL MUS LD50 2119 mg/kg
 ORL RAT LD50 4300 mg/kg
 SCU RAT LD50 1700 mg/kg
 - TERT-BUTYL ACETATE
 ORL RAT LD50 4100 mg/kg
 SKN RBT LD50 >2 gm/kg
 - ISOBUTANOL
 IVN MUS LD50 417 mg/kg
 IVN RAT LD50 340 mg/kg
 ORL RAT LD50 2460 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

- Disposal operations:** D1 Tipping above or underground (e.g. landfill, etc.).
 R1 Solvent reclamation/regeneration.

SAFETY DATA SHEET

UP0741V ACID #8 AEROSOL MIR COMPLIANT

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1950 **ADR Class:** 2
Classification code: 5F
Shipping name: AEROSOLS
Labelling: 2.1



IMDG / IMO

UN no: 1950 **Class:** 2
EmS: F-D,S-U **Marine pollutant:** .
Labelling: 2.1

IATA / ICAO

UN no: 1950 **Class:** 2
Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.
 Irritant.



Risk phrases: R12: Extremely flammable.
 R36: Irritating to eyes.
 R66: Repeated exposure may cause skin dryness or cracking.
 R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.
 S16: Keep away from sources of ignition - No smoking.
 S23: Do not breathe vapour/spray
 S38: In case of insufficient ventilation, wear suitable respiratory equipment.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

SAFETY DATA SHEET

UP0741V ACID #8 AEROSOL MIR COMPLIANT

VbF: All

Water hazard class: 1

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R11: Highly flammable.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.
R12: Extremely flammable.
R10: Flammable.
R22: Harmful if swallowed.
R37/38: Irritating to respiratory system and skin.
R41: Risk of serious damage to eyes.
R20/21: Harmful by inhalation and in contact with skin.
R38: Irritating to skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.