

## Safety Data Sheet

Printing date 05/12/2015

Revised On 05/12/2015

## 1 Identification of the substance and manufacturer

**Trade name:** RUBBERIZED UNDERCOATING  
**Product code:** 51333  
**Product category:** PC9a Paints and coatings.  
**Manufacturer/Supplier:** Quest Automotive Products  
 600 Nova Drive SE  
 Massillon, OH 44646  
 phone: 330-830-6000  
 www.quest-ap.com  
**Emergency telephone number:** ChemTrec: 800-424-9300

## 2 Hazard(s) identification

## Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Carc. 2 H351 Suspected of causing cancer.  
 Repr. 2 H361 Suspected of damaging fertility or the unborn child.  
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.  
 Eye Irrit. 2A H319 Causes serious eye irritation.

## GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

## Signal word

## Hazard statements

Danger  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.  
 Suspected of causing cancer.  
 Suspected of damaging fertility or the unborn child.  
 May cause damage to organs through prolonged or repeated exposure.  
 If medical advice is needed, have product container or label at hand.  
 Keep out of reach of children.  
 Read label before use.

## Precautionary statements

Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Wash hands thoroughly after handling.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Do not handle until all safety precautions have been read and understood.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Get medical advice/attention if you feel unwell.  
 IF exposed or concerned: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 Store in a well-ventilated place.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

## Chemical characterization: Mixtures

## Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

## Dangerous components:

8052-42-4	Asphalt	19.62%
74-98-6	propane	12.6%
1317-65-3	Calcium Carbonate	11.5%
1332-58-7	Aluminum Silicate	7.66%
106-97-8	n-butane	7.4%
64742-47-8	Mineral Spirits	3.37%
108-88-3	Toluene	3.37%
67-56-1	methanol	1.92%

## 4 First-aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.  
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.  
**After swallowing:** Rinse mouth with water. Do not induce vomiting.  
**Most important symptoms and effects:** Dizziness  
**Indication of any immediate medical attention needed:** No further relevant information available.

## 5 Fire-fighting measures

**Extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray.

(Contd. on page 2)

## Safety Data Sheet

Printing date 05/12/2015

Revised On 05/12/2015

Trade name: RUBBERIZED UNDERCOATING

**Special hazards:**

Can form explosive gas-air mixtures.

(Contd. of page 1)

**Protective equipment for firefighters:**

A respiratory protective device may be necessary.

**6 Accidental release measures****Personal precautions, protective equipment and emergency procedures:**

Use respiratory protective device against the effects of fumes/dust/aerosol.

**Methods and material for containment and cleaning up:**

Absorb liquid components with liquid-binding material.

**7 Handling and storage****Precautions for safe handling**

Use only in well ventilated areas.

**Storage requirements:**

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****8052-42-4 Asphalt**REL (USA) Ceiling limit value: 5\* mg/m<sup>3</sup>  
\*15-min; See Pocket Guide App. ATLV (USA) Long-term value: 0.5\* mg/m<sup>3</sup>  
\*inh. fraction; as benzene-soluble aerosol; BEI<sub>p</sub>**74-98-6 propane**PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppmREL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

TLV (USA) refer to Appendix F

**1332-58-7 Aluminum Silicate**PEL (USA) Long-term value: 15\* 5\*\* mg/m<sup>3</sup>  
\*total dust \*\*respirable fractionREL (USA) Long-term value: 10\* 5\*\* mg/m<sup>3</sup>  
\*total dust \*\*respirable fractionTLV (USA) Long-term value: 2\* mg/m<sup>3</sup>  
E; as respirable fraction**106-97-8 n-butane**REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppmTLV (USA) Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm**108-88-3 Toluene**PEL (USA) Long-term value: 200 ppm  
Ceiling limit value: 300; 500\* ppm  
\*10-min peak per 8-hr shiftREL (USA) Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 375 mg/m<sup>3</sup>, 100 ppmTLV (USA) Long-term value: 75 mg/m<sup>3</sup>, 20 ppm  
BEI**67-56-1 methanol**PEL (USA) Long-term value: 260 mg/m<sup>3</sup>, 200 ppmREL (USA) Short-term value: 325 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 260 mg/m<sup>3</sup>, 200 ppm  
SkinTLV (USA) Short-term value: 328 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 262 mg/m<sup>3</sup>, 200 ppm  
Skin; BEI**Ingredients with biological limit values:****8052-42-4 Asphalt**BEI (USA) -  
Medium: urine  
Time: end of shift at end of workweek  
Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)**108-88-3 Toluene**

(Contd. on page 3)

## Safety Data Sheet

Printing date 05/12/2015

Revised On 05/12/2015

Trade name: RUBBERIZED UNDERCOATING

(Contd. of page 2)

BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

**67-56-1 methanol**

BEI (USA)	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----------	---

<b>Hygienic protection:</b>	Immediately remove all soiled and contaminated clothing. Wash hands after use. Do not eat or drink while working.
<b>Breathing equipment:</b>	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
<b>Hand protection:</b>	Protective gloves. The glove material must be impermeable and resistant to the substance.
<b>Eye protection:</b>	Tightly sealed goggles

**9 Physical and chemical properties**

<b>Appearance:</b>	Aerosol.
<b>Odor:</b>	Aromatic
<b>Odor threshold:</b>	Not determined.
<b>pH-value:</b>	Not determined.
<b>Melting point/Melting range</b>	Undetermined.
<b>Boiling point:</b>	-44 °C (-47 °F)
<b>Flash point:</b>	-19 °C (-2 °F)
<b>Flammability (solid, gas):</b>	Extremely flammable.
<b>Decomposition temperature:</b>	Not determined.
<b>Auto igniting:</b>	Product is not self-igniting.
<b>Danger of explosion:</b>	In use, may form flammable/explosive vapour-air mixture.
<b>Lower Explosion Limit:</b>	1.7 Vol %
<b>Upper Explosion Limit:</b>	10.9 Vol %
<b>Vapor pressure:</b>	Not determined.
<b>Relative Density:</b>	Between 0.77 and 0.85 (Water equals 1.00)
<b>Vapour density</b>	Not determined.
<b>Evaporation rate</b>	Not applicable.
<b>Partition coefficient: n-octanol/water:</b>	Not determined.
<b>Solubility:</b>	Not determined.
<b>Viscosity:</b>	Not determined.
<b>VOC content:</b>	365.5 g/l / 3.05 lb/gl
<b>VOC content (less exempt solvents):</b>	28.6 %
<b>Water:</b>	31.0 %
<b>MIR Value:</b>	0.30
<b>Solids content:</b>	40.4 %

**10 Stability and reactivity**

<b>Reactivity:</b>	Stable at normal temperatures.
<b>Conditions to avoid:</b>	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
<b>Chemical stability:</b>	Not fully evaluated.
<b>Possibility of hazardous reactions:</b>	No dangerous reactions known.
<b>Incompatible materials:</b>	No further relevant information available.
<b>Hazardous decomposition:</b>	No dangerous decomposition products known.

**11 Toxicological information**

LD/LC50 values that are relevant for classification:

**106-97-8 n-butane**

Inhalative LC50/4 h 658 mg/l (rat)

**67-56-1 methanol**

Oral LD50 13000 mg/kg (rat)

**Information on toxicological effects:** No data available.**Skin effects:** No irritant effect.

(Contd. on page 4)

## Safety Data Sheet

Printing date 05/12/2015

Revised On 05/12/2015

Trade name: RUBBERIZED UNDERCOATING

(Contd. of page 3)

**Eye effects:** No irritating effect.  
**Sensitization:** No sensitizing effects known.

**Carcinogenic categories****IARC (International Agency for Research on Cancer)**

8052-42-4	Asphalt	2B
108-88-3	Toluene	3

**NTP (National Toxicology Program)**

None of the ingredients is listed.

**12 Ecological information**

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Other adverse effects:** No further relevant information available.

**13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
**Recommendation:** Completely empty cans should be recycled.

**14 Transport information**

**UN-Number** UN1950  
**DOT** N/A  
**DOT** Consumer Commodity ORM-D  
 Aerosols, flammable  
 1950 Aerosols  
**ADR**  
**Transport hazard class(es):**  
**Class** 2.1  
**Marine pollutant:** No  
**Special precautions for user:** Warning: Gases  
**EMS Number:** F-D,S-U  
**Quantity limitations** On passenger aircraft/rail: 75 kg  
 On cargo aircraft only: 150 kg

---

**ADR**  
**Excepted quantities (EQ)** Code: E0  
 Not permitted as Excepted Quantity

---

**IMDG**  
**Limited quantities (LQ)** 1L  
**Excepted quantities (EQ)** Code: E0  
 Not permitted as Excepted Quantity

**Packaging Group:** --  
**UN "Model Regulation":** UN1950, Aerosols, 2.1

**15 Regulatory information****SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

108-88-3	Toluene
67-56-1	methanol

**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

None of the ingredients in this product are listed.

**California Proposition 65 chemicals known to cause developmental toxicity:**

108-88-3	Toluene
67-56-1	Methanol

**CANADIAN ENVIRONMENTAL PROTECTION ACT:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

**EPA:**

108-88-3	Toluene	II
----------	---------	----

**16 Other information**

**Contact:** Regulatory Affairs  
**Date of preparation / last revision** 05/12/2015 / -