



Safety Data Sheet acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

1 Identification

- **Product identifier**
- **Trade name:** GTB420 BASECOAT BINDER
- **Article number:** GTB420
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Lusid Technologies
5195 West 4700 South
KEARNS, UT 84118
USA
www.lusid.biz
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: **GTB420 BASECOAT BINDER**

(Contd. of page 1)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



HEALTH 2 Health = 2

FIRE 3 Fire = 3

REACTIVITY 0 Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

USA

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: GTB420 BASECOAT BINDER

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	50-100%
110-43-0	heptan-2-one	2.5-10%
67-64-1	acetone	≤2.5%
100-41-4	ethylbenzene	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: GTB420 BASECOAT BINDER

(Contd. of page 3)

· Protective Action Criteria for Chemicals
· PAC-1:

110-43-0	heptan-2-one	150 ppm
67-64-1	acetone	200 ppm
1330-20-7	xylene	130 ppm
119-64-2	1,2,3,4-tetrahydronaphthalene	1.6 ppm
100-41-4	ethylbenzene	33 ppm
123-42-2	4-hydroxy-4-methylpentan-2-one	150 ppm

· PAC-2:

110-43-0	heptan-2-one	670 ppm
67-64-1	acetone	3200* ppm
1330-20-7	xylene	920* ppm
119-64-2	1,2,3,4-tetrahydronaphthalene	17 ppm
100-41-4	ethylbenzene	1100* ppm
123-42-2	4-hydroxy-4-methylpentan-2-one	350 ppm

· PAC-3:

110-43-0	heptan-2-one	4000* ppm
67-64-1	acetone	5700* ppm
1330-20-7	xylene	2500* ppm
119-64-2	1,2,3,4-tetrahydronaphthalene	100 ppm
100-41-4	ethylbenzene	1800* ppm
123-42-2	4-hydroxy-4-methylpentan-2-one	2100* ppm

7 Handling and storage

· Handling:

· **Precautions for safe handling** No special precautions are necessary if used correctly.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities
· Storage:

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· Control parameters
· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: GTB420 BASECOAT BINDER

(Contd. of page 4)

At this time, the remaining constituent has no known exposure limits.

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 233 mg/m³, 50 ppm

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm

Long-term value: 594 mg/m³, 250 ppm

BEI

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 87 mg/m³, 20 ppm

BEI

· Ingredients with biological limit values:
67-64-1 acetone

BEI 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: GTB420 BASECOAT BINDER

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

Color:

Whitish

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined (pH N/A in solvent coatings)

· **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

55 °C (131 °F)

· **Flash point:**

-17 °C (1.4 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

533 °C (991.4 °F)

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:

Not determined.

Upper:

Not determined.

· **Vapor pressure:**

Not determined.

· **Density at 20 °C (68 °F):**

1.2533 g/cm³ (10.4588 lbs/gal)

· **Relative density**

Not determined.

· **Vapor density**

Not determined.

· **Evaporation rate**

Not determined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: GTB420 BASECOAT BINDER

(Contd. of page 6)

- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 11.8 %
 - VOC content:** 9.97 %
124.9 g/l / 1.04 lb/gal
- **Solids content:** 14.0 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

USA

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: GTB420 BASECOAT BINDER

(Contd. of page 7)



12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | UN1263 |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA | Paint
PAINT |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center;">  <p>3</p> </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids
3 |
| <ul style="list-style-type: none"> · IMDG, IATA | |
| <ul style="list-style-type: none"> · Class | <div style="text-align: center;">  <p>3</p> </div> <p>3 Flammable liquids</p> |

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: GTB420 BASECOAT BINDER

(Contd. of page 8)

· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

100-41-4 ethylbenzene

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4 ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: GTB420 BASECOAT BINDER

(Contd. of page 9)

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D

- **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: GTB420 BASECOAT BINDER

(Contd. of page 10)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Product Safety Dept.
- **Date of preparation / last revision** 08/06/2018 / 2
- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 2: Carcinogenicity – Category 2

- *** Data compared to the previous version altered.**

USA