



Page 1/14

USA

Reviewed on 02/22/2016

1 Identification

- · Product identifier
- · Trade name: 13003-13023 Clear Aerosol
- · Article number: 13003, 13013, 13023
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

• Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.

GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.

GHS08 Health hazard

V	
Carc. 2	H351 Suspected of causing cancer.
Repr. 2	H361 Suspected of damaging fertility or the unborn child.
STOT RE 2	H373 May cause damage to organs through prolonged or repeated exposure.
Skin Irrit. 2 Eye Irrit. 2A Skin Sens. 1 STOT SE 3	507 H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.
· Label element: · GHS label eler	

Printing date 02/22/2016

Reviewed on 02/22/2016

SEM

Trade name: 13003-13023 Clear Aerosol

· Hazard pictogra	(Contd. of page 1)
, when he had	
GHS02 GHS	S04 GHS07 GHS08
011502 011	504 011507 011500
· Signal word Da	inger
· Hazard-determ	ining components of labeling:
acetone	
toluene	
4-methylpentan	-2-one
butanone	
 Hazard stateme 	nts
H222 Extremely	y flammable aerosol.
H280 Contains	gas under pressure; may explode if heated.
H315 Causes sk	
H319 Causes se	prious eye irritation.
H317 May caus	e an allergic skin reaction.
	l of causing cancer.
	l of damaging fertility or the unborn child.
	e drowsiness or dizziness.
	e damage to organs through prolonged or repeated exposure.
• Precautionary s	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P211	Do not spray on an open flame or other ignition source.
P280	Wear protective gloves.
P280	Wear eye protection / face protection.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P303+P351+P.	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
D201	and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 P363	Call a POISON CENTER/doctor if you feel unwell. Wash contaminated clothing before rause
	Wash contaminated clothing before reuse.
P308+P313 P333+P313	IF exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P314	<i>Get medical advice/attention if you feel unwell.</i>
P302+P352	IF ON SKIN: Wash with plenty of water.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
1 105 11 255	(Contd. on page 3)
	USA




SEM

Page 3/14

Reviewed on 02/22/2016

Trade name: 13003-13023 Clear Aerosol



· Chemical characterization: Mixtures

· Description:

Mixture: consisting of the following components. Weight percentages

· Dangerous	components:	
67-64-1		40 - 60%
74-98-6	propane	13 - 30%
108-88-3		7 - 10%
110-19-0	isobutyl acetate	7 - 10%
108-10-1	4-methylpentan-2-one	5 - 7%
	butanone	1.5 - 5%
108-65-6	2-methoxy-1-methylethyl acetate	1.5 - 5%
	ethyl 3-ethoxypropionate	1-1.5%
2807-30-9	2-(propyloxy)ethanol	1-1.5%


4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)



SEM

Page 4/14

Reviewed on 02/22/2016

Trade name: 13003-13023 Clear Aerosol

• Information for doctor:

(Contd. of page 3)

- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- · Precautions for safe handling
- No special measures required. Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- Information about protection against explosions and fires: Do not spray on a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Observe official regulations on storing packagings with pressurized containers.
- Information about storage in one common storage facility: Store away from oxidizing agents.
- $\cdot \textit{Further information about storage conditions: Keep receptacle tightly sealed.}$

(Contd. on page 5)

SEM Reviewed on 02/22/2016

Printing date 02/22/2016

Trade name: 13003-13023 Clear Aerosol

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

Compo	onents with limit values that require monitoring at the workplace:	
67-64-	1 acetone	
PEL	Long-term value: 2400 mg/m³, 1000 ppm	
REL	Long-term value: 590 mg/m³, 250 ppm	
TLV	Short-term value: 1187 mg/m³, 500 ppm	
	Long-term value: 594 mg/m ³ , 250 ppm	
74.00	BEI	
	6 propane	
PEL	Long-term value: 1800 mg/m ³ , 1000 ppm	
REL	Long-term value: 1800 mg/m ³ , 1000 ppm	
TLV	refer to Appendix F inTLVs and BEIs book	
	8-3 toluene	
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm	
	*10-min peak per 8-hr shift	
REL	Short-term value: 560 mg/m ³ , 150 ppm	
	Long-term value: 375 mg/m ³ , 100 ppm	
TLV	Long-term value: 75 mg/m³, 20 ppm BEI	
110-19	9-0 isobutyl acetate	
PEL	Long-term value: 700 mg/m ³ , 150 ppm	
REL	Long-term value: 700 mg/m³, 150 ppm	
TLV	Short-term value: NIC-712 mg/m³, NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm	
108-10)-1 4-methylpentan-2-one	
PEL	Long-term value: 410 mg/m ³ , 100 ppm	
REL	Short-term value: 300 mg/m³, 75 ppm Long-term value: 205 mg/m³, 50 ppm	
TLV	Short-term value: 307 mg/m³, 75 ppm	
	Long-term value: 82 mg/m³, 20 ppm BEI	
78-93-	3 butanone	
PEL	Long-term value: 590 mg/m ³ , 200 ppm	
REL	Short-term value: 885 mg/m ³ , 300 ppm	
	Long-term value: 590 mg/m ³ , 200 ppm	
TLV	Short-term value: 885 mg/m^3 , 300 ppm	
	Long-term value: 590 mg/m³, 200 ppm BEI	
		(Contd. on pag

(Contd. of page 4)

Printing date 02/22/2016

SEM Reviewed on 02/22/2016

Trade name: 13003-13023 Clear Aerosol

108-	65-6 2-methoxy-1-methylethyl acetate (Contd. of page :
	EL Long-term value: 50 ppm
· Ingr	edients with biological limit values:
-	i4-1 acetone
BEI	50 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)
108-	88-3 toluene
BEI	0.02 mg/L
	Medium: blood
	Time: prior to last shift of workweek
	Parameter: Toluene
	0.03 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Toluene
	0.3 mg/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: o-Cresol with hydrolysis (background)
108-	10-1 4-methylpentan-2-one
BEI	1 mg/L
	Medium: urine
	Time: end of shift
	Parameter: MIBK
78-9	3-3 butanone
BEI	2 mg/L
	Medium: urine
	Time: end of shift
	Parameter: MEK
· Add	itional information: The lists that were valid during the creation were used as basis.
· Exn	osure controls
-	conal protective equipment:
	eral protective and hygienic measures:
	p away from foodstuffs, beverages and feed.
Imm	ediately remove all soiled and contaminated clothing.
Was	h hands before breaks and at the end of work.
	e protective clothing separately.
	id contact with the eyes and skin.
	thing equipment:
	ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure u
	<i>iratory protective device that is independent of circulating air.</i>
	fection of hands:
Due	to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the
	nical mixture.



SEM

Page 7/14

(Contd. of page 6)

Reviewed on 02/22/2016

Trade name: 13003-13023 Clear Aerosol

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Safety glasses



Tightly sealed goggles

· Information on basic physical and chemical properties				
General Information				
Appearance:				
Form:	Aerosol			
Color:	According to product specification			
Odor:	Characteristic			
Odor threshold:	Not determined.			
pH-value:	Not determined.			
Change in condition				
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	-44 °C			
Flash point:	-97 °C			
Flammability (solid, gaseous):	Not applicable.			
Ignition temperature:	405 °C			
Decomposition temperature:	Not determined.			
Auto igniting:	Product is not selfigniting.			
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.			
Explosion limits:				
Lower:	1.7 Vol %			
Upper:	13.0 Vol %			
Vapor pressure at 20 °C:	8300 hPa			
Density at 20 °C:	0.75255 g/cm ³			

Printing date 02/22/2016

Reviewed on 02/22/2016

Trade name: 13003-13023 Clear Aerosol

	(Con	td. of page
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/w	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	92.0 %	
VOC content:	51.6 %	
	631.7 g/l / 5.27 lb/gl	
Solids content:	8.2 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:
- Nitrogen oxides
- *Hydrocarbons*

Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:


108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative		5320 mg/l (mouse)

· Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 9)



SEM

Page 9/14

Reviewed on 02/22/2016

Trade name: 13003-13023 Clear Aerosol

(Contd. of page 8)

3

2B

3

· Curcinogenic culegories	•	Carcino	genic	categories	
---------------------------	---	---------	-------	------------	--

· IARC (International Agency for Research on Cancer)

108-88-3 toluene

108-10-1 4-methylpentan-2-one

111-76-2 2-butoxyethanol

·NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

• **Recommendation:** Disposal must be made according to official regulations.

· UN-Number		
· DOT, ADR, IMDG, IATA	UN1950	
· UN proper shipping name		
· DOT, IATA	Aerosols, flammable	
· ADR	1950 Aerosols	
·IMDG	AEROSOLS	

[·] Uncleaned packagings:



Page 10/14

Reviewed on 02/22/2016

Printing date 02/22/2016

Trade name: 13003-13023 Clear Aerosol

	(Contd. of page
Transport hazard class(es)	
DOT	
2	
Class	2.1
Label	2.1
ADR	
Class	2 5F Gases
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
Packing group DOT, ADR, IMDG, IATA	Void
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Gases
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre
	Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clear of livir
	quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litra
	Segregation as for class 9. Stow "separated from" class 1 except for
	division 1.4. For AEROSOLS with a capacity above 1 litre
	Segregation as for the appropriate subdivision of class 2. Fo WASTE AEROSOLS: Segregation as for the appropriate subdivisio
	of class 2.
Transport in bulk according to Annex	•
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 75 kg
	On cargo aircraft only: 150 kg
	(Contd. on page



Page 11/14

Reviewed on 02/22/2016

Printing date 02/22/2016

Trade name:	13003-13023	Clear Aerosol
-------------	-------------	---------------

		(Contd. of page 10
· Remarks	ORM-D CFR49 173.150,156,306	
· ADR		
\cdot Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
· IMDG		
\cdot Limited quantities (LQ)	1L	
\cdot Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1	

*

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355	(extremely hazardous substances):
None of the	ingredient is listed.
· Section 313	(Specific toxic chemical listings):
108-88-3 ta	oluene
108-10-1 4	-methylpentan-2-one
78-93-3 b	utanone
111-76-2 2	-butoxyethanol
· TSCA (Tox	ic Substances Control Act):
67-64-	1 acetone
74-98-	6 propane
108-88-	3 toluene
110-19-	0 isobutyl acetate
108-10-	1 4-methylpentan-2-one
78-93-	3 butanone
	6 2-methoxy-1-methylethyl acetate
763-69-	9 ethyl 3-ethoxypropionate
	9 2-(propyloxy)ethanol
41556-26-	7 bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate
104810-48-	2 alpha-3-(3-(2H-Benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega hydroxypoly(oxy-ethylen)
104810-47-	1 alpha-3-(2H-Benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl)-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylen)
111-76-	2 2-butoxyethanol
9038-95-	3 OXIRANE, ME, POLYMER
82919-37-	7 Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate
· Proposition	
· Chemicals	known to cause cancer:
108-10-1 4	-methylpentan-2-one
	(Contd. on page



Page 12/14

Reviewed on 02/22/2016

Printing date 02/22/2016

Trade name: 13003-13023 Clear Aerosol

108-88-3 to	to a serie a series de stine de si e iter for formales.	(Contd. of page
108-88-3 10	nown to cause reproductive toxicity for females:	
	nown to cause reproductive toxicity for males:	
None of the	ingredients is listed.	
Chemicals k	nown to cause developmental toxicity:	
108-88-3 to	luene	
108-10-1 4-	methylpentan-2-one	
Cancerogen	ity categories	
EPA (Envir	onmental Protection Agency)	
67-64-1 a	U I	I
108-88-3 to		
	methylpentan-2-one	I
78-93-3 bi	• •	
	butoxyethanol	N
	-	1
	hold Limit Value established by ACGIH)	
67-64-1 a		A
108-88-3 to		A
111-76-2 2-	butoxyethanol	A
	GHS04 GHS07 GHS08	
· Signal word · Hazard-dete		
• Signal word • Hazard-dete acetone	Danger	
• Signal word • Hazard-dete acetone toluene	Danger ermining components of labeling:	
• Signal word • Hazard-dete acetone toluene 4-methylpen	Danger ermining components of labeling:	
• Signal word • Hazard-dete acetone toluene 4-methylpen butanone	Danger ermining components of labeling: tan-2-one	
• Signal word • Hazard-dete acetone toluene 4-methylpen butanone • Hazard state H222 Extren	Danger ermining components of labeling: tan-2-one ements nely flammable aerosol.	
• Signal word • Hazard-dete acetone toluene 4-methylpen butanone • Hazard stat H222 Extren H280 Conta	Danger ermining components of labeling: tan-2-one ements nely flammable aerosol. ins gas under pressure; may explode if heated.	
• Signal word • Hazard-dete acetone toluene 4-methylpen butanone • Hazard state H222 Extrep H280 Conta H315 Cause	Danger ermining components of labeling: tan-2-one ements nely flammable aerosol. ins gas under pressure; may explode if heated. es skin irritation.	
Signal word Hazard-dete acetone toluene 4-methylpen butanone Hazard state H222 Extree H280 Conta H315 Cause H319 Cause	Danger ermining components of labeling: tan-2-one ements nely flammable aerosol. ins gas under pressure; may explode if heated. is skin irritation.	
Signal word Hazard-dete acetone toluene 4-methylpen butanone Hazard state H222 Extree H280 Conta H315 Cause H319 Cause H317 May c	Danger ermining components of labeling: tan-2-one ements nely flammable aerosol. ins gas under pressure; may explode if heated. is skin irritation. is serious eye irritation. is serious eye irritation. is ause an allergic skin reaction.	
Signal word Hazard-dete acetone toluene 4-methylpen butanone Hazard state H222 Extree H280 Conta H315 Cause H319 Cause H317 May C H351 Suspe	Danger ermining components of labeling: tan-2-one ements nely flammable aerosol. ins gas under pressure; may explode if heated. es skin irritation. s serious eye irritation. ause an allergic skin reaction. cted of causing cancer.	
Signal word Hazard-dete acetone toluene 4-methylpen butanone Hazard state H222 Extree H280 Conta H315 Cause H319 Cause H317 May c H351 Suspe H361 Suspe H336 May c	Danger ermining components of labeling: etan-2-one ements nely flammable aerosol. ins gas under pressure; may explode if heated. es skin irritation. es serious eye irritation. ause an allergic skin reaction. cted of causing cancer. cted of damaging fertility or the unborn child. ause drowsiness or dizziness.	
Signal word Hazard-dete acetone toluene 4-methylpen butanone Hazard stat H222 Extree H280 Conta H315 Cause H319 Cause H317 May c H351 Suspe H361 Suspe H366 May c H373 May c	Danger prmining components of labeling: tan-2-one ements nely flammable aerosol. ins gas under pressure; may explode if heated. es skin irritation. es serious eye irritation. ause an allergic skin reaction. cted of causing cancer. cted of damaging fertility or the unborn child. ause drowsiness or dizziness. ause damage to organs through prolonged or repeated exposure.	
Signal word Hazard-dete acetone toluene 4-methylpen butanone Hazard stat H222 Extree H280 Conta H315 Cause H319 Cause H317 May o H351 Suspe H361 Suspe H360 May o H373 May o	Danger ermining components of labeling: etan-2-one ements nely flammable aerosol. ins gas under pressure; may explode if heated. es skin irritation. es serious eye irritation. ause an allergic skin reaction. cted of causing cancer. cted of damaging fertility or the unborn child. ause drowsiness or dizziness.	quadring

P251 Do not pierce or burn, even after use.

(Contd. on page 13)



Reviewed on 02/22/2016

Printing date 02/22/2016

Trade name: 13003-13023 Clear Aerosol

	(Contd. of page 12)
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P211	Do not spray on an open flame or other ignition source.
P280	Wear protective gloves.
P280	Wear eye protection / face protection.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P305+P351+P33	8 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P363	Wash contaminated clothing before reuse.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver (sgaver@semproducts.com)
- · Date of preparation / last revision 02/22/2016 / 9

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)
- *LC50: Lethal concentration, 50 percent*

(Contd. on page 14)

[•] Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

USA

Printing date 02/22/2016



Reviewed on 02/22/2016

Trade name: 13003-13023 Clear Aerosol

	(Contd. of page 13)
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flam. Aerosol 1: Flammable aerosols, Hazard Category 1	
Press. Gas: Gases under pressure: Compressed gas	
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2	
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A	
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1	
Carc. 2: Carcinogenicity, Hazard Category 2	
Repr. 2: Reproductive toxicity, Hazard Category 2	
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3	
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2	
• * Data compared to the previous version altered.	

Page 14/14