

Printing date 02/22/2016 Reviewed on 01/08/2016

#### 1 Identification

· Product identifier

· Trade name: 38403 Blenz In

· Article number: 38403

· Application of the substance / the mixture Coating

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust\_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

#### 2 Hazard(s) identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Muta. 1A H340 May cause genetic defects.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)

IISA



Reviewed on 01/08/2016

Trade name: 38403 Blenz In

(Contd. of page 1)

#### · Hazard pictograms









GHS04

GHS07

#### · **Signal word** Danger

#### · Hazard-determining components of labeling:

Petroleum gases, liquefied, sweetened acetone

toluene

#### · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H312 Harmful in contact with skin.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### . Precautionary statements

· 1 recumiona	ry statements
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P211	Do not spray on an open flame or other ignition source.
P280	Wear protective gloves / protective clothing.
P280	Wear eye protection / face protection.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and under

erstood.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340

Call a POISON CENTER/doctor if you feel unwell. P312 P308+P313 IF exposed or concerned: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P314 Get medical advice/attention if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water. P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding* 50°C/122°F.

Store in a well-ventilated place. Keep container tightly closed. P403+P233

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

(Contd. on page 3)



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 38403 Blenz In

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 4 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous	· Dangerous components:					
108-94-1	cyclohexanone	40 - 60%				
68476-86-8	Petroleum gases, liquefied, sweetened	13 - 30%				
67-64-1	acetone	13 - 30%				
108-88-3	toluene	1.5 - 5%				
<i>763-69-9</i>	ethyl 3-ethoxypropionate	1.5 - 5%				
	NJ TSRN: 8009285004 Polyester Plasticizer	1-1.5%				

## 4 First-aid measures

- · Description of first aid measures
- · General information:

*Immediately remove any clothing soiled by the product.* 

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 38403 Blenz In

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- $\cdot \textit{Specific end use}(s) \textit{ No further relevant information available}.$

HSA.



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 38403 Blenz In

(Contd. of page 4)

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components	with lin	nit values	that r	reauire	monitoring	at the	worknlace:
Components	<i>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</i>	iii ruiuc.	, iiiui i	cyunc	IIIOIIIIOI III S	ui iii	wormpuice.

#### 108-94-1 cyclohexanone

PEL Long-term value: 200 mg/m³, 50 ppm

REL Long-term value: 100 mg/m³, 25 ppm

Skin

TLV Long-term value: 50 mg/m³, 20 ppm

Skin

#### 67-64-1 acetone

PEL Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm

BEI

#### 108-88-3 toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500\* ppm

\*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm

BEI

#### · Ingredients with biological limit values:

#### 108-94-1 cyclohexanone

BEI 80 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: 1.2-Cyclohexanediol with hydrolysis (nonspecific, semi-quantitative)

8 mg/L

Medium: urine Time: end of shift

Parameter: Cyclohexanol with hydrolysis (nonspecific, semi-quantitative)

#### 67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 6)

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 38403 Blenz In

(Contd. of page 5)

#### 108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

 $0.03 \, mg/L$ Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eve protection:

Safety glasses

(Contd. on page 7)

SEM

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 38403 Blenz In

(Contd. of page 6)



Tightly sealed goggles

T.O T T	
Information on basic physical and	chemical properties
General Information	
· Appearance:	Aerosol
Form: Color:	According to product specification
Cowr: Odor:	Characteristic
· Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C
Flash point:	-103 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	420 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.3 Vol %
Upper:	13.0 Vol %
Vapor pressure at 20 °C:	233 hPa
Density at 20 °C:	$0.77118 \text{ g/cm}^3$
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	t <b>er</b> ): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	96.4 %
VOC content:	78.4 %
	733.2 g/l / 6.12 lb/gl

(Contd. on page 8)



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 38403 Blenz In

(Contd. of page 7)

Solids content: 3.7 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· <i>LD/LC50</i> ı	· LD/LC50 values that are relevant for classification:				
108-94-1 с	yclohexan	one			
Oral	LD50	1535 mg/kg (rat)			
Dermal	<i>LD50</i>	948 mg/kg (rabbit)			
Inhalative	LC50/4 h	8000 mg/l (rat)			
108-88-3 te	oluene				
Oral	LD50	5000 mg/kg (rat)			
Dermal	<i>LD50</i>	12124 mg/kg (rabbit)			
Inhalative	LC50/4 h	5320 mg/l (mouse)			

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (In	· IARC (International Agency for Research on Cancer)				
108-94-1	cyclohexanone	3			
108-88-3	toluene	3			
· NTP (Nat	· NTP (National Toxicology Program)				
None of th	None of the ingredients is listed.				

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

USA

SEM

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 38403 Blenz In

(Contd. of page 8)

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

7 4 7	T.		C	
14	ranspor	t ını	orma	ากท

	UN	$-N_1$	umb	er
--	----	--------	-----	----

· DOT, ADR, IMDG, IATA UN1950

· UN proper shipping name

DOT, IATA
Aerosols, flammable
ADR
1950 Aerosols
IMDG
AEROSOLS

- · Transport hazard class(es)
- $\cdot DOT$



- · Class 2.1
- · *Label* 2.1

(Contd. on page 10)

SEM

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 38403 Blenz In

(Contd. of page 9)  $\cdot ADR$ 2 5F Gases · Class · Label 2.1 · IMDG, IATA 2.1 · Class · Label 2.1 · Packing group · DOT, ADR, IMDG, IATA Void · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Gases · EMS Number: F-D,S-U· Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: · Segregation Code Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information:  $\cdot DOT$ · Quantity limitations On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg  $\cdot ADR$ · Excepted quantities (EQ) Not permitted as Excepted Quantity · IMDG · Limited quantities (LQ) 1LCode: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity

(Contd. on page 11)



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 38403 Blenz In

(Contd. of page 10)

· UN ''Model Regulation'': UN 1950 AEROSOLS, 2.1

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

						_
•	Section	355	(extremely	hazardous	substances):	•

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3 toluene

· TSCA (Toxic Substances Control Act):

108-94-1 cyclohexanone

68476-86-8 Petroleum gases, liquefied, sweetened

67-64-1 acetone

108-88-3 toluene

763-69-9 ethyl 3-ethoxypropionate

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

108-88-3 toluene

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3 toluene

· Cancerogenity categories

· EPA (Environmental Protection	on Agency)
---------------------------------	------------

67-64-1	acetone	I
108-88-3	toluene	II

#### · TLV (Threshold Limit Value established by ACGIH)

108-94-1	cyclohexanone	<i>A3</i>
67-64-1	acetone	A4
108-88-3	toluene	A4

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02 GH

GHS04

GHS07

CHICOO

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 38403 Blenz In

(Contd. of page 11)

#### · Signal word Danger

#### · Hazard-determining components of labeling:

Petroleum gases, liquefied, sweetened

acetone

### toluene

P321

#### · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H312 Harmful in contact with skin.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Precautionary statements

1 recumonary statements	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P211	Do not spray on an open flame or other ignition source.
P280	Wear protective gloves / protective clothing.
P280	Wear eye protection / face protection.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and under

rstood.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Specific treatment (see on this label).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell. P312 P308+P313 IF exposed or concerned: Get medical advice/attention. P337+P313 *If eye irritation persists: Get medical advice/attention.* P314 Get medical advice/attention if you feel unwell. P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

Protect from sunlight. Store in a well-ventilated place. P410+P403

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Store in a well-ventilated place. Keep container tightly closed. P403+P233

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver (sgaver@semproducts.com)
- · Date of preparation / last revision 02/22/2016 / 7

(Contd. on page 13)

SEM

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 38403 Blenz In

(Contd. of page 12)

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

 $BEI: Biological\ Exposure\ Limit$ 

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas Acute Tox. 4: Acute toxicity, Hazard Category 4

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Muta. 1A: Germ cell mutagenicity, Hazard Category 1A Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

\* \* Data compared to the previous version altered.

USA