Printing date 02/22/2016 Reviewed on 01/08/2016

1 Identification

- · Product identifier
- · Trade name: 39063 Gloss Trim Black Aerosol
- · Article number: 39063
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc.

1685 Overview Drive

Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com: SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730: phone 1-800-831-

1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Muta. 1A H340 May cause genetic defects. Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 1)

· Hazard pictograms









GHS04

GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Petroleum gases, liquefied, sweetened

toluene acetone

ethyl acetate

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
------	--

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray. P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves.

P280 Wear eye protection / face protection. P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P301+P310

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell. P308+P313 IF exposed or concerned: Get medical advice/attention. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell. P314

Do NOT induce vomiting. P331

P302+P352 IF ON SKIN: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse. P362+P364

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

(Contd. on page 3)



Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 2)

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1Fire = 4Reactivity = 3

· HMIS-ratings (scale 0 - 4)



Health = *1Fire = 4

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous	components:	
67-64-1	acetone	30 - 40%
68476-86-8	Petroleum gases, liquefied, sweetened	13 - 30%
108-88-3	toluene	13 - 30%
	ethyl acetate	7 - 10%
763-69-9	ethyl 3-ethoxypropionate	5 - 7%
<i>78-93-3</i>	butanone	5 - 7%
108-65-6	2-methoxy-1-methylethyl acetate	1.5 - 5%
	NJ TSRN: 8009285004 Polyester Plasticizer	1.5 - 5%
1333-86-4	Carbon black	≤1%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- \cdot Specific end use(s) No further relevant information available.

IIS A

SEM

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 4)

	onal information about design of technical systems: No further data; see item 7.
	ol parameters onents with limit values that require monitoring at the workplace:
	1 acetone
PEL	Long-term value: 2400 mg/m³, 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI
108-88	3-3 toluene
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm
TLV	Long-term value: 75 mg/m³, 20 ppm BEI
141-78	8-6 ethyl acetate
PEL	Long-term value: 1400 mg/m³, 400 ppm
REL	Long-term value: 1400 mg/m³, 400 ppm
TLV	Long-term value: 1440 mg/m³, 400 ppm
78-93-	3 butanone
PEL	Long-term value: 590 mg/m³, 200 ppm
REL	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm
TLV	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm BEI
108-65	5-6 2-methoxy-1-methylethyl acetate
WEEL	Long-term value: 50 ppm
Ingrea	lients with biological limit values:
	1 acetone
N	0 mg/L 1edium: urine
	ïme: end of shift Parameter: Acetone (nonspecific)

(Contd. on page 6)

USA

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 5)

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

 $0.03 \, mg/L$ Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI 2 mg/L

Medium: urine Time: end of shift Parameter: MEK

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

SEM

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 6)

· Eye protection: Safety glasses



Tightly sealed goggles

Information on basic physical and	chamical proporties
· Information on basic physical and · General Information	cnemical properties
· Appearance:	
Form:	Aerosol
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C
· Flash point:	< -17 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	460 °C
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	13.0 Vol %
· Vapor pressure at 20 °C:	233 hPa
Density at 20 °C:	0.74654 g/cm^3
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	t er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	92.8 %

(Contd. on page 8)



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 39063 Gloss Trim Black Aerosol

 VOC content:
 62.8 %

 654.4 g/l / 5.46 lb/gl

 Solids content:
 7.8 %

 Other information
 No further relevant information available.

*

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Nitrogen oxides

Hydrocarbons

Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 v	· LD/LC50 values that are relevant for classification:		
108-88-3 to	108-88-3 toluene		
Oral	LD50	5000 mg/kg (rat)	
Dermal	LD50	12124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5320 mg/l (mouse)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)			
108-88-3	toluene	3	
1333-86-4	Carbon black	2B	
111-76-2	2-butoxyethanol	3	
NTD /N J' I T' . I D			

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 9)

SEM

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 8)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA

UN1950

- · UN proper shipping name
- \cdot **DOT**, **IATA**

Aerosols, flammable

 $\cdot ADR$

1950 Aerosols

· ADK · IMDG

- **AEROSOLS**
- · Transport hazard class(es)
- $\cdot DOT$



· Class 2.1

(Contd. on page 10)

SEM

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 39063 Gloss Trim Black Aerosol

	(Contd. of page
Label	2.1
ADR	
2	
Class	2 5F Gases
Label	2.1
IMDG, IATA	
<u>w</u>	
2	
Class	2.1
Label	2.1
Packing group	
DOT, ADR, IMDG, IATA	Void
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Gases
EMS Number:	F-D,S-U SWI Protected from sources of heat
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litr.
	Category A. For AEROSOLS with a capacity above 1 litro
	Category B. For WASTE AEROSOLS: Category C, Clear of livin
Segregation Code	quarters. SG69 For AEROSOLS with a maximum capacity of 1 litr.
Segregation Code	Segregation as for class 9. Stow "separated from" class 1 except for
	division 1.4. For AEROSOLS with a capacity above 1 litr
	Segregation as for the appropriate subdivision of class 2. For
	WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex	· ·
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 75 kg
	On cargo aircraft only: 150 kg
Remarks	ORM-D 49CFR-173-150,156, 306
ADR	a
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
	Not permitted as Excepted Quantity
IMDG Limited quantities (LQ)	IL
Limitea quantities (LQ)	(Contd. on page



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 39063 Gloss Trim Black Aerosol

· Excepted quantities (EQ)
Code: E0
Not permitted as Excepted Quantity
· UN ''Model Regulation'':
UN 1950 AEROSOLS, 2.1

Regulatory information	
Safety, health and environmental regulations/legislation specific for the substance Sara	or mixture
Section 355 (extremely hazardous substances):	
None of the ingredient is listed.	
Section 313 (Specific toxic chemical listings):	
108-88-3 toluene	
78-93-3 butanone	
111-76-2 2-butoxyethanol	
TSCA (Toxic Substances Control Act):	
67-64-1 acetone	
68476-86-8 Petroleum gases, liquefied, sweetened	
108-88-3 toluene	
141-78-6 ethyl acetate	
763-69-9 ethyl 3-ethoxypropionate	
78-93-3 butanone	
108-65-6 2-methoxy-1-methylethyl acetate	
1333-86-4 Carbon black	
111-76-2 2-butoxyethanol	
9038-95-3 OXIRANE, ME, POLYMER	
Proposition 65	
Chemicals known to cause cancer:	
1333-86-4 Carbon black	
Chemicals known to cause reproductive toxicity for females:	
108-88-3 toluene	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
108-88-3 toluene	
Cancerogenity categories	
EPA (Environmental Protection Agency)	
67-64-1 acetone	
108-88-3 toluene	
78-93-3 butanone	

(Contd. on page 12)



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 11)

		(Conta. of page 11)
· TLV (Thre	shold Limit Value established by ACGIH)	
67-64-1	acetone	A4
108-88-3	toluene	A4
1333-86-4	Carbon black	A4
111-76-2	2-butoxyethanol	A3
· NIOSH-Co	(National Institute for Occupational Safety and Health)	
1333-86-4	Carbon black	

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS04

GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Petroleum gases, liquefied, sweetened

toluene

acetone

ethyl acetate

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves.

P280 Wear eye protection / face protection. P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.
P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 13)

SEM

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 12) P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P314 Get medical advice/attention if you feel unwell. Do NOT induce vomiting. P331 P302+P352 *IF ON SKIN:* Wash with plenty of water. P362+P364 Take off contaminated clothing and wash it before reuse. P405 Store locked up. P410+P403 Protect from sunlight. Store in a well-ventilated place. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P403+P233 Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local/regional/national/international P501 regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver (sgaver@semproducts.com)
- · Date of preparation / last revision 02/22/2016 / 7
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Muta. 1A: Germ cell mutagenicity, Hazard Category 1A

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

* * Data compared to the previous version altered.