

1 Identification

- **Product identifier**
- **Trade name:** 39133 Flexible Primer Surfacer
- **Article number:** 39133
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 2 H371 May cause damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS04 GHS07 GHS08

· Signal word *Danger*

· Hazard-determining components of labeling:

Quartz (SiO₂)

acetone

toluene

titanium dioxide

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H371 May cause damage to organs.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves.

P280 Wear eye protection / face protection.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P308+P313 IF exposed or concerned: Get medical advice/attention.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

- **Dangerous components:**

68476-86-8	Petroleum gases, liquefied, sweetened	13 - 30%
67-64-1	acetone	13 - 30%
14808-60-7	Quartz (SiO ₂)	13 - 30%
1330-20-7	xylene	10 - 13%
110-19-0	isobutyl acetate	7 - 10%
108-88-3	toluene	1.5 - 5%
123-86-4	n-butyl acetate	1.5 - 5%
13463-67-7	titanium dioxide	1.5 - 5%
78-93-3	butanone	1.5 - 5%
14807-96-6	Talc	≤1%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)



Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

USA

(Contd. on page 5)



Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 4)

8 Exposure controls/personal protection

· *Additional information about design of technical systems: No further data; see item 7.*

· *Control parameters*

· *Components with limit values that require monitoring at the workplace:*

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm
 REL Long-term value: 590 mg/m³, 250 ppm
 TLV Short-term value: 1187 mg/m³, 500 ppm
 Long-term value: 594 mg/m³, 250 ppm
 BEI

14808-60-7 Quartz (SiO₂)

PEL see Quartz listing
 REL Long-term value: 0.05* mg/m³
 *respirable dust; See Pocket Guide App. A
 TLV Long-term value: 0.025* mg/m³
 *as respirable fraction

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm
 REL Short-term value: 655 mg/m³, 150 ppm
 Long-term value: 435 mg/m³, 100 ppm
 TLV Short-term value: 651 mg/m³, 150 ppm
 Long-term value: 434 mg/m³, 100 ppm
 BEI

110-19-0 isobutyl acetate

PEL Long-term value: 700 mg/m³, 150 ppm
 REL Long-term value: 700 mg/m³, 150 ppm
 TLV Short-term value: NIC-712 mg/m³, NIC-150 ppm
 Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm

108-88-3 toluene

PEL Long-term value: 200 ppm
 Ceiling limit value: 300; 500* ppm
 *10-min peak per 8-hr shift
 REL Short-term value: 560 mg/m³, 150 ppm
 Long-term value: 375 mg/m³, 100 ppm
 TLV Long-term value: 75 mg/m³, 20 ppm
 BEI

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm
 REL Short-term value: 950 mg/m³, 200 ppm
 Long-term value: 710 mg/m³, 150 ppm
 TLV Short-term value: (950) NIC-712 mg/m³, (200) NIC-150 ppm
 Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm

(Contd. on page 6)



Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 5)

78-93-3 butanone

PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI

· Ingredients with biological limit values:

67-64-1 acetone

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI	2 mg/L Medium: urine Time: end of shift Parameter: MEK
-----	---

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

(Contd. on page 7)

Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 6)

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Aerosol
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	55 °C

· **Flash point:** -103 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 405 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

(Contd. on page 8)



Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 7)

· Explosion limits:	
Lower:	1.1 Vol %
Upper:	13.0 Vol %
· Vapor pressure at 20 °C: 233 hPa	
· Density at 20 °C: 0.81629 g/cm ³	
· Relative density Not determined.	
· Vapor density Not determined.	
· Evaporation rate Not applicable.	
· Solubility in / Miscibility with Water: Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	77.4 %
VOC content:	57.4 %
	590.6 g/l / 4.93 lb/gl
· Solids content: 22.6 %	
· Other information No further relevant information available.	

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
1330-20-7 xylene		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
108-88-3 toluene		
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

(Contd. on page 9)



Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 8)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14808-60-7	Quartz (SiO ₂)	1
1330-20-7	xylene	3
108-88-3	toluene	3
13463-67-7	titanium dioxide	2B
14807-96-6	Talc	2B
7631-86-9	silicon dioxide, chemically prepared	3
1333-86-4	Carbon black	2B
111-76-2	2-butoxyethanol	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE	
------------	---	--

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.




(Contd. on page 10)

Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 9)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number · DOT, ADR, IMDG, IATA	UN1950
· UN proper shipping name · DOT, IATA · ADR · IMDG	Aerosols, flammable 1950 Aerosols AEROSOLS
· Transport hazard class(es) · DOT	
	
· Class · Label	2.1 2.1
· ADR	
	
· Class · Label	2 5F Gases 2.1
· IMDG, IATA	
	
· Class · Label	2.1 2.1
· Packing group · DOT, ADR, IMDG, IATA	Void
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · EMS Number:	Warning: Gases F-D,S-U

(Contd. on page 11)



Trade name: 39133 Flexible Primer Surfacer

(Contd. of page 10)

· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· ADR	
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
	ACRYLIC RESIN
108-88-3	toluene
78-93-3	butanone
14807-96-6	Talc
111-76-2	2-butoxyethanol
100-41-4	ethylbenzene
67-56-1	methanol

· **TSCA (Toxic Substances Control Act):**

68476-86-8	Petroleum gases, liquefied, sweetened
67-64-1	acetone

(Contd. on page 12)



Trade name: 39133 Flexible Primer Surfacer

(Contd. of page 11)

14808-60-7	Quartz (SiO ₂)
1330-20-7	xylene
110-19-0	isobutyl acetate
108-88-3	toluene
123-86-4	n-butyl acetate
13463-67-7	titanium dioxide
78-93-3	butanone
14807-96-6	Talc
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
7631-86-9	silicon dioxide, chemically prepared
21645-51-2	aluminium hydroxide
51274-00-1	YELLOW IRON OXIDE

· Proposition 65

· Chemicals known to cause cancer:

14808-60-7	Quartz (SiO ₂)
1330-20-7	xylene
13463-67-7	titanium dioxide
1333-86-4	Carbon black
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

108-88-3	toluene
----------	---------

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3	toluene
67-56-1	methanol

· Cancerogenity categories

· EPA (Environmental Protection Agency)

67-64-1	acetone	I
1330-20-7	xylene	I
108-88-3	toluene	II
78-93-3	butanone	I
111-76-2	2-butoxyethanol	NL
100-41-4	ethylbenzene	D

· TLV (Threshold Limit Value established by ACGIH)

67-64-1	acetone	A4
14808-60-7	Quartz (SiO ₂)	A2
1330-20-7	xylene	A4
108-88-3	toluene	A4
13463-67-7	titanium dioxide	A4

(Contd. on page 13)

Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 12)

14807-96-6	Talc	A4
1333-86-4	Carbon black	A4
111-76-2	2-butoxyethanol	A3
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO ₂)
13463-67-7	titanium dioxide
1333-86-4	Carbon black
67-56-1	methanol

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Quartz (SiO₂)

acetone

toluene

titanium dioxide

· **Hazard statements**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H371 May cause damage to organs.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves.

P280 Wear eye protection / face protection.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P308+P313 IF exposed or concerned: Get medical advice/attention.

P332+P313 If skin irritation occurs: Get medical advice/attention.

(Contd. on page 14)

Trade name: 39133 Flexible Primer Surfacer

(Contd. of page 13)

P337+P313 *If eye irritation persists: Get medical advice/attention.*
 P314 *Get medical advice/attention if you feel unwell.*
 P302+P352 *IF ON SKIN: Wash with plenty of water.*
 P362+P364 *Take off contaminated clothing and wash it before reuse.*
 P405 *Store locked up.*
 P410+P403 *Protect from sunlight. Store in a well-ventilated place.*
 P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.*
 P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** *Environment protection department.*

· **Contact:** *Steve Gaver (sgaver@semproducts.com)*

· **Date of preparation / last revision** *02/22/2016 / 7*

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Carc. 1A: Carcinogenicity, Hazard Category 1A

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 2: Specific target organ toxicity - Single exposure, Hazard Category 2

(Contd. on page 15)



Printing date 02/22/2016

Reviewed on 11/17/2015

Trade name: 39133 Flexible Primer Surfacer

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
· *** Data compared to the previous version altered.**

(Contd. of page 14)

USA