Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/05/2011 Revised On 01/05/2011

1 Identification of the substance and manufacturer

Trade name: **BIG RIG CUMMINS BEIGE**

Product code: 0000201647

Manufacturer/Supplier: SEYMOUR OF SYCAMORE

917 Crosby Avenue Sycamore, IL 60178

(815)-895-9101, www.seymourpaint.com CHEMTEL 1-800-255-3924, 813-248-0585 Emergency telephone number: *if located outside the U.S.*



2 Composition/information on ingredients

Chemical Description: This product is a mixture of the substances listed below with pophagardous additions

_	Officialical Description.	This product is a mixture of the substances listed below with normazardods additions.
Dangerous components:		
Γ	67-64-1 Acetone	35.28%
	74-98-6 propane	15.82%
	106-97-8 n-butane	9.29%
	2807-30-9 Glycol Ether EP	6.07%
	108-10-1 methyl isobutyl ketone	ne 5.61%
	13463-67-7 titanium dioxide	4.81%
	107-87-9 Methyl Propyl Ketone	9 4.36%
	110-19-0 isobutyl acetate	1.59%
	96-29-7 2-butanone oxime	0.1%

3 Hazards identification

Hazard Information: Extremely flammable liquid and vapor. Keep away from heat, sparks, and flame.

Has narcotizing effect.

Risk phrases: Extremely flammable.

Irritating to eyes.

Vapours may cause drowsiness and dizziness

Keep out of the reach of children. Safety phrases:

Keep away from sources of ignition - No smoking. Do not breathe gas/fumes/vapour/spray.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

The International Agency for Research on Cancer has evaluated ethylbenzene and classified it a possible human Special precautions:

carcinogen based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. However, a two year rat and mouse gavage study by the National Toxicology Program on mixed xylene isomers including 17% ethylbenzene showed no evidence of carcinogenicity.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. Effects of chronic overexposure:

NFPA ratings (0 - 4):

Health = Fire =

Reactivity = 3 HMIS-ratings (0 - 4): Health=

Physical Hazard= 3

4 First aid measures

After inhalation:

Supply fresh air; consult doctor in case of complaints.
Remove contaminated clothing. Wash exposed area with soap and water.
Move to fresh air. Rinse opened eye for several minutes under running water. After skin contact: After eye contact: After swallowing:

Contact physician or poison control center.

5 Firefighting measures

Extinguishing agents: CO2, sand, extinguishing powder, or water spray. No further relevant information available. Special hazards:

Protective equipment: No special measures required

6 Accidental release measures

Personal safety procedures: Wear protective equipment. Keep unprotected persons away. Environmental precautions: Additional precautions: Do not allow product to reach sewage systems or ground water. Ensure adequate ventilation.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities.

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/05/2011 Revised On 01/05/2011

Trade name: BIG RIG CUMMINS BEIGE

(Contd. of page 1)

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL 2400 mg/m³, 1000 ppm REL 590 mg/m³, 250 ppm TLV Short-term value: 1782 mg/m³, 750 ppm Long-term value: 1188 mg/m³, 500 ppm BFI

74-98-6 propane

PEL 1800 mg/m³, 1000 ppm REL 1800 mg/m³, 1000 ppm TLV Varies mg/m³, 1000 ppm

106-97-8 n-butane

REL 1900 mg/m³, 800 ppm TLV Varies mg/m³, 1000 ppm

108-10-1 methyl isobutyl ketone

PEL 410 mg/m³, 100 ppm
REL Short-term value: 300 mg/m³, 75 ppm
Long-term value: 205 mg/m³, 50 ppm
TLV Short-term value: 307 mg/m³, 75 ppm
Long-term value: (205) 82 mg/m³, (50) NIC-20 ppm
(BEI);NIC-A3

107-87-9 Methyl Propyl Ketone

PEL 700 mg/m³, 200 ppm REL 530 mg/m³, 150 ppm TLV Short-term value: 529 mg/m³, 150 ppm

110-19-0 isobutyl acetate

PEL 700 mg/m³, 150 ppm REL 700 mg/m³, 150 ppm TLV 713 mg/m³, 150 ppm

Hygienic protection: Breathing equipment:

Keep away from foodstuffs and animal feed. Wash hands after use.

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure

Hand protection:

conditions exist, please consult an authority on chemical hygeine. Protective gloves. The glov recommendation can be given. The glove material has to be impermeable and resistant to the substance. No glove

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

Odor: Aromatic pH-value: Boiling point: Not determined. -44°C (-47°F) -19°C (-2°F) Flash point:

Auto igniting: Product is not self-igniting.

Danger of explosion:

Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % **Upper Explosion Limit:** 10.9 Vol % Vapor Pressure: 40 PSI, 2750 hPa

Specific Gravity: Between 0.77 and 0.85 (Water equals 1.00)

594.0 g/l / 4.96 lb/gl

VOC content: $$594.0\ \mbox{\scriptsize g}$$ VOC content (less exempt solvents): $43.2\ \%$ MIR Value: 1.06Solids content: 35.1 %

Other information No further relevant information available.

10 Stability and reactivity

Conditions to avoid: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

Hazardous reactions: No dangerous reactions known.

No dangerous decomposition products known. Hazardous decomposition:

11 Toxicological information

Skin effects: No irritant effect. Eye effects: Irritating effect.

Sénsitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons Other information:

(PFC's), or chlorinated solvents.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

(Contd. on page 3)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/05/2011 Revised On 01/05/2011

Trade name: BIG RIG CUMMINS BEIGE

Recommendation: Completely empty cans should be recycled. (Contd. of page 2)

14 Transport information

Hazard class: Identification number: N/A Label

2.1+8 2 5FC Gases ADR/RID/TDG class:

1950 **UN-Number:** IMDG Class: 2.1 īī Packaging group: EMS Number: F-D,S-U Marine pollutant: ICAO/IATA Class: No

Special marking: Consumer Commodity ORM-D

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-10-1 methyl isobutyl ketone

All ingredients are listed.

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. CPSC:

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

CANADIAN ENVIRONMENTAL

PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

WHMIS Symbols for Canada: Compressed gas

D2B - Toxic material causing other toxic effects

Corrosive material

EPA: B= Probable human carcinogen A= Known human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

'Data are inádequate for an assessment of human carcinogeni potential.' 'Inadequate information to assess carcinogenic potential.'

67-64-1 Acetone 108-10-1 methyl isobutyl ketone 110-19-0 isobutyl acetate D

Group 2A: The ingredient is probably carcinogenic to humans.
Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.
Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans. IARC:

13463-67-7 titanium dioxide

A1-designates a confirmed human carcinogen. ACGIH:

A2-designates a suspected human carcinogen. A3-designates an animal carcinogen.

A4-designates "not classifiable as a human carcinogen".

67-64-1 Acetone A4 13463-67-7 titanium dioxide Α4 110-19-0 isobutyl acetate A4

NIOSH: The following substances are regulated in the United States with reference to occupational exposure limits:

13463-67-7 titanium dioxide

1333-86-4 Carbon black

Hazard symbols:



Irritant

Extremely flammable

16 Other information

This product was manufactured in the U.S.A.
The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Regulatory Affairs Contact:

Abbreviations and acronyms:

REGUIATORY AITAITS

GHS: Globally Harmonized System of Classification and Labelling of Chemicals CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) VOC: Volatile Organic Compounds (USA, EU)

HMIS: Hazardous Materials Identification System (USA)

EPA: Environmental Protection Agency (PARC: International Agency for the Research of Cancer NIOSH: National Institute for Occupational Safety and Health TSCA: Toxic Substances Control Act

CPSC: Consumer Product Safety Commission

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

ISO: International Organization for Standardization

2B