

TECHNICAL DATA SHEET

www.refinishsolutionsgroup.com

PART NUMBER

REVvive by RSG - Satin Trim Black

666233**91013**

PACKAGE SIZE

Aerosol, 15.2 fl. oz. / Net Wt. 10.9 oz.

6/case

DESCRIPTION

Restores original Satin Black appearance to body panels, under hood, chassis and wheels. Excellent pigment density, essentially single-coat coverage. Apply direct to TPO, EDPM, and polypropylene without an adhesion promotor.



SUBSTRATES: Can be applied to OEM-painted surfaces, lightly abraded E-Coat, TPO, EDPM, and polypropylene.

SURFACE PREPARATION: For best results, ensure the surface is thoroughly cleaned, degreased, dried and dust free. Sand primed surfaces wet or dry with 400-600 grit sandpaper, degrease and dry.

MIXING: Shake the aerosol can for at least 2 minutes before use.

COATS: 1 - 2 coats at a distance of approx. 6 - 10 inches from the surface gives a build thickness of 15μ / 0.6 MIL.

THEORETICAL COVERAGE: 48 ft²/unit

(theoretical coverage per unit assuming 100% transfer efficiency and giving the dry film thickness between indicated values.)

TECHNICAL DATA

FLASH OFF: 3 - 5 minutes between coats

DRYING TIME: Dust-free @ 68 °F: 20 - 30 minutes

VOC INFORMATION: Maximum Incremental Reactivity (MIR): 1.70 (Automotive Bumper and Trim Product)

STORAGE INFORMATION

SHELF LIFE: 2 years from manufacture subject to good storage conditions.

Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry, well-ventilated area and away from direct sunlight and frost. To maximize the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use to clear the nozzle. If the nozzle becomes blocked, remove it from the can and soak it in gentle thinners.

RECOMMENDED STORAGE TEMPERATURE: 41 °F - 77 °F RECOMMENDED APPLICATION TEMPERATURE: 68 °F

PRECAUTIONS

For use only by professional use only. Before use, read and follow all TDS, label and SDS precautions.

