

Reviewed on 02/26/2013

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: HR010 Hot Rod Black Kit with HR014, HRC06 & HRR06
- · Article number: HR010 Kit
- *Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.*
- \cdot Application of the substance / the preparation coating

Details of the supplier of the safety data sheet
Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

• Emergency telephone number: 24 HR EMERGENCY CHEMTREC 1-800-424-9300

2 Hazards identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. *Muta.* 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· Label elements

- · GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).
- · Hazard pictograms GHS02, GHS08
- · Signal word Danger
- *Hazard-determining components of labelling:* 1,6-HEXAMETHYLENE DIISOCYANATE Solvent naphtha (petroleum), light arom.

• *Hazard statements* H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

(Contd. on page 2)

⁻ USA

SEM

Safety Data Sheet acc. to ISO/DIS 11014

Printing date 02/26/2013

Reviewed on 02/26/2013

Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06

	(Contd. of page 1)
H319 Causes serie	pus eye irritation.
H334 May cause a	allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause a	in allergic skin reaction.
H340 May cause g	genetic defects.
H350 May cause d	cancer.
· Precautionary sta	tements
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P303+P361+P35	3 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P33	8 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Classification syst	
· NFPA ratings (sc	
Fire	alth = 2 $a = 3$ $ctivity = 0$
· HMIS-ratings (sc	ale 0 - 4)
FIRE 3 Fil	alth = *2 re = 3 activity = 0
 Other hazards Results of PBT and PBT: Not applicant vPvB: Not applicant 	

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

	ACRYLIC RESIN	13 - 30%
	𝚯 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H336	1
123-86-4	n-butyl acetate	13 - 30%
	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	1
67-64-1	acetone	13 - 30%
	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336	1
112-07-2	2-butoxyethyl acetate	7 - 10%
	() Acute Tox. 4, H312; Acute Tox. 4, H332; H227	1
28182-81-2	1,6-HEXAMETHYLENE DIISOCYANATE	7 - 10%
	& Resp. Sens. 1, H334; STOT SE 2, H371; (Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	1

Printing date 02/26/2013

Reviewed on 02/26/2013

Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06

		ontd. of page
108-65-6	2-methoxy-1-methylethyl acetate	5 - 7%
	🚸 Flam. Liq. 3, H226	1
9004-36-8	CELLULOSE ACETATE BUTYRATE	1.5 - 5%
	① Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	1
	Silica	
	🚸 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	1
110-43-0	heptan-2-one	1.5 - 5%
	🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 4, H302; Acute Tox. 4, H332	1
108-83-8	2,6-dimethylheptan-4-one	1.5 - 5%
	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H335	1
1330-20-7	xylene	1-1.5%
	🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	1
14807-96-6	Talc	1-1.5%
	🚸 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	1
19549-80-5	4,6-dimethylheptan-2-one	1-1.5%
	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H335	1
64742-95-6	Solvent naphtha (petroleum), light arom.	1-1.5%
	🛞 Flam. Liq. 3, H226; 🚸 Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304	1
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate	<u>≤</u> 1%
	🚸 Skin Irrit. 2, H315; Skin Sens. 1, H317	1
95-63-6	1,2,4-trimethylbenzene	≤1%
108-67-8	mesitylene	<i>≤1%</i>
	🛞 Flam. Liq. 3, H226; 🚸 STOT SE 3, H335	1

4 First aid measures

· Description of first aid measures

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 4)

USA

[•] General information:





Page 4/12

Reviewed on 02/26/2013

Trade name: HR010 Hot Rod Black Kit with HR014, HRC06 & HRR06

(Contd. of page 3)

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** No special measures required. Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- \cdot Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

USA



Reviewed on 02/26/2013

SEM

Trade name: HR010 Hot Rod Black Kit with HR014, HRC06 & HRR06

Contr	ol parameters	
	on parameters	
-	5-4 n-butyl acetate	
PEL	710 mg/m ³ , 150 ppm	
REL	Short-term value: 950 mg/m ³ , 200 ppm	
	Long-term value: 710 mg/m ³ , 150 ppm	
TLV	Short-term value: 950 mg/m³, 200 ppm Long-term value: 713 mg/m³, 150 ppm	
67-64-	1 acetone	
PEL	2400 mg/m ³ , 1000 ppm	
REL	590 mg/m ³ , 250 ppm	
TLV	Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-475 mg/m³, (500) NIC-200 ppm BEI	
112-02	-2 2-butoxyethyl acetate	
REL	33 mg/m ³ , 5 ppm	
TLV	130 mg/m³, 20 ppm	
108-65	-6 2-methoxy-1-methylethyl acetate	
WEEL	50 ppm	
110-4	B-0 heptan-2-one	
PEL	465 mg/m ³ , 100 ppm	
REL	465 mg/m³, 100 ppm	
TLV	233 mg/m³, 50 ppm	
108-8.	-8 2,6-dimethylheptan-4-one	
PEL	290 mg/m ³ , 50 ppm	
REL	150 mg/m³, 25 ppm	
TLV	145 mg/m³, 25 ppm	
1330-2	20-7 xylene	
PEL	435 mg/m ³ , 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI	
Ingrea	lients with biological limit values:	
67-64-	1 acetone	
N T	0 mg/L ledium: urine ime: end of shift arameter: Acetone (nonspecific)	
	20-7 xylene	
1000		(Contd. on pag

Printing date 02/26/2013

Safety Data Sheet acc. to ISO/DIS 11014



Page 6/12

Reviewed on 02/26/2013

Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06

BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids - • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. Protection of hands: Implies Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ chemical mixture. Selection of the gloves material on consideration of the penetration times, rates of diffusion and the degradation? Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality varies from manufactur		(Contd. of page 5
Time: end of shift Parameter: Methylhippuric acids • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective equipment: • General protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. • Protection of hands: • Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation. • Selection of the gloves material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistand of the glove material can not be calculated in advance and has therefore to be checked prior to the application • Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to • Septertion inter of gloves and has to be found out by the manufacturer of the protective gloves and has to • Septertion: • Penetration time of glove material can be be found out by the manufacturer of the protective gloves and has to • Septertion: • Pertoretion:		
Parameter: Methylhippuric acids • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. • Protection of hands: • Or protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ chemical mixture. Selection of the suitable gloves does not only depend on the material, but also on further marks of quality varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistant of the glove material can not be calculated in advance and has therefore to be checked prior to the application of the glove material can not be calculated in advance and has therefore to be checked prior to the application of the glove material can not be calculated in advance and has therefore to be checked prior to the application of the glove material can to be found out by the m		
Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ chemical mixture. Selection of the gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistant of the glove material can not be calculated in advance and has therefore to be checked prior to the application Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to observed. Eye protection:		
Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ chemical mixture. Selection of the suitable gloves does not only depend on the material, but also on further marks of quality varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistand of the glove material can not be calculated in advance and has therefore to be checked prior to the application Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Experimential to the sub to be found out by the manufacturer of the protective gloves and has to be solved.		· · ·
Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. Protection of hands:	Addi	tional information: The lists that were valid during the creation were used as basis.
General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. Protection of hands:	Expo	osure controls
Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. Protection of hands:	Perso	onal protective equipment:
Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. Protection of hands:	Gene	eral protective and hygienic measures:
 Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/chemical mixture. Selection of the gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistant of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to observed. Eye protection: 	Keep	away from foodstuffs, beverages and feed.
Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. Protection of hands:	Imme	ediately remove all soiled and contaminated clothing.
Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. Protection of hands:	Wash	hands before breaks and at the end of work.
Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. Protection of hands:		
Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. Protection of hands: Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ chemical mixture. Selection of the suitable gloves does not only depend on the material, but also on further marks of quality varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistant of the glove material can not be calculated in advance and has therefore to be checked prior to the application Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to observed. Eye protection:		
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. Protection of hands:		
respiratory protective device that is independent of circulating air. Protection of hands:		
Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistant of the glove material can not be calculated in advance and has therefore to be checked prior to the application Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to observed. Eye protection:		
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistant of the glove material can not be calculated in advance and has therefore to be checked prior to the application Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to observed. Eye protection:	Prote	ection of hands:
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistant of the glove material can not be calculated in advance and has therefore to be checked prior to the application Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to observed. Eye protection:	" "	Protective gloves
Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to observed. Eye protection:	Due	to missing tests no recommendation to the glove material can be given for the product/ the preparation/ th
varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistances of the glove material can not be calculated in advance and has therefore to be checked prior to the application Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to observed. Eye protection:		
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to observed. Eye protection:	The s varie of the	selection of the suitable gloves does not only depend on the material, but also on further marks of quality an es from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance e glove material can not be calculated in advance and has therefore to be checked prior to the application.
	The e	exact break trough time has to be found out by the manufacturer of the protective gloves and has to b
Tightly sealed goggles		
Tightly sealed goggles		
		Tightly sealed goggles
Physical and chemical properties	Phy	sical and chemical properties
· Information on basic physical and chemical properties		

- · General Information
- · Appearance: Form:
- Form:LiquidColor:According to product specificationOdor:CharacteristicOdour threshold:Not determined.• pH-value:Not determined.

(Contd. on page 7)

USA

Printing date 02/26/2013

Reviewed on 02/26/2013

SE

Trade name: HR010 Hot Rod Black Kit with HR014, HRC06 & HRR06

	(Contd. of page
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 55 °C
· Flash point:	-18 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	280 °C
· Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits: Lower: Upper:	1.2 Vol % 13.0 Vol %
• Vapor pressure at 20 •C:	233 hPa
• Density at 20 °C: • Relative density • Vapour density • Evaporation rate	0.97 g/cm ³ Not determined. Not determined. Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water	"): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
Solvent content: Organic solvents: VOC content:	54.5 % 25.8 % 424.6 g/l / 3.54 lb/gl
Solids content: • Other information	45.5 % No further relevant information available.

10 Stability and reactivity

· Reactivity

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.


· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 8)



SEM

Page 8/12

Reviewed on 02/26/2013

Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06

(Contd. of page 7)

LD/LC50	values that	are relevant for classification:	
		AMETHYLENE DIISOCYANATE	
Oral	LD50	1000 mg/kg (rat)	
Dermal	LD50	5000 mg/kg (rabbit)	
Inhalative	LC50/4 h	137-1150 mg/l (rat)	
64742-95-	6 Solvent n	aphtha (petroleum), light arom.	
Oral	LD50	>6800 mg/kg (rat)	
Dermal	LD50	>3400 mg/kg (rab)	
Inhalative	LC50/4 h	>10.2 mg/l (rat)	
Sensitizatio Additional The produc Harmful	on: on possible on possible l toxicologi	through inhalation. through skin contact. cal information: e following dangers according to internally approved calculd	ntion methods for preparation
Sensitizatia Sensitizatia Additional The product Harmful Irritant Carcinoge The product Carcinoge	on: on possible on possible I toxicologi ct shows th nic. ct can caus nic catego	through inhalation. through skin contact. cal information: e following dangers according to internally approved calcula e inheritable damage. ries	tion methods for preparation
Sensitizatia Sensitizatia Additional The product Harmful Irritant Carcinoge The product Carcinoge IARC (International Contemporation of the	on: on possible on possible I toxicologi ct shows th nic. ct can caus nic catego ernational	through inhalation. through skin contact. cal information: e following dangers according to internally approved calcula e inheritable damage.	
Sensitizatia Sensitizatia Additional The product Harmful Irritant Carcinoge The product Carcinoge IARC (Intel 1330-20-	on: on possible on possible I toxicologi ct shows th nic. ct can caus nic catego ernational 7 xylene	through inhalation. through skin contact. cal information: e following dangers according to internally approved calcula e inheritable damage. ries	3
Sensitizatia Sensitizatia Additional The product Harmful Irritant Carcinoge Carcinoge IARC (Inta 1330-20- 14807-96-	on: on possible on possible toxicologi ct shows th nic. ct can caus nic catego ernational 7 xylene 6 Talc	through inhalation. through skin contact. cal information: e following dangers according to internally approved calcula e inheritable damage. ries Agency for Research on Cancer)	3
Sensitizatia Sensitizatia Additional The product Harmful Irritant Carcinoge The product Carcinoge IARC (Int. 1330-20- 14807-96- 1333-86-	on: on possible on possible I toxicologi ct shows th nic. ct can caus nic catego ernational 7 xylene 6 Talc 4 Carbon	through inhalation. through skin contact. cal information: e following dangers according to internally approved calcula e inheritable damage. ries Agency for Research on Cancer) black	3 21 21 21
Sensitizatia Sensitizatia Sensitizatia Additional The product Harmful Irritant Carcinoge Carcinoge IARC (Intel 1330-20- 14807-96-0 1333-86-0 9002-88-0	on: on possible on possible toxicologi ct shows th nic. ct can caus nic catego ernational 7 xylene 6 Talc 4 Carbon 4 POLYET	through inhalation. through skin contact. cal information: e following dangers according to internally approved calcula e inheritable damage. ries Agency for Research on Cancer) black THYLENE	3 21 21 3
Sensitizatia Sensitizatia Additional The product Harmful Irritant Carcinoge The product Carcinoge IARC (Intel 1330-20- 14807-96- 1333-86- 9002-88- 100-41-	on: on possible on possible I toxicologi ct shows th nic. ct can caus mic catego ernational 7 xylene 6 Talc 4 Carbon 4 POLYET 4 ethylben	through inhalation. through skin contact. cal information: e following dangers according to internally approved calcula e inheritable damage. ries Agency for Research on Cancer) black THYLENE	3 2 2 2

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

(Contd. on page 9)



Printing date 02/26/2013

Reviewed on 02/26/2013

Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06

(Contd. of page 8)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. • Results of PBT and vPvB assessment

• *PBT*: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

· UN-Number	
DOT, ADR, IMDG, IATA	UN1263
· UN proper shipping name · DOT, IMDG, IATA · ADR	PAINT 1263 PAINT, special provision 640D
· Transport hazard class(es)	
·DOT	
FLAMMER E LOUID	
· Class · Label	3 Flammable liquids. 3
· ADR, IMDG, IATA	5
· Class	3 Flammable liquids
· Label	3
· Packing group · DOT, ADR, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
Special precautions for user EMS Number:	Warning: Flammable liquids F-E, <u>S-E</u>
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.

Printing date 02/26/2013

Reviewed on 02/26/2013

Trade name: HR010 Hot Rod Black Kit with HR014, HRC06 & HRR06

· UN ''Model Regulation'':

UN1263, PAINT, special provision 640D, 3, II

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
Sara
Section 355 (extremely hazardous substances):

None of the ingredient is listed.

• Section 313 (Specific toxic chemical listings): ACRYLIC RESIN

1330-20-7 xylene

14807-96-6 Talc 95-63-6 1,2,4-trimethylbenzene

98-82-8 cumene

100-41-4 ethylbenzene

• TSCA (Toxic Substances Control Act):

123-86-4 n-butyl acetate 67-64-1 acetone

112-07-2 2-butoxyethyl acetate

28182-81-2 1,6-HEXAMETHYLENE DIISOCYANATE

108-65-6 2-methoxy-1-methylethyl acetate

9004-36-8 CELLULOSE ACETATE BUTYRATE

110-43-0 heptan-2-one

108-83-8 2,6-dimethylheptan-4-one 1330-20-7 xylene

14807-96-6 Talc

19549-80-5 4,6-dimethylheptan-2-one

64742-95-6 Solvent naphtha (petroleum), light arom.

123-42-2 4-hydroxy-4-methylpentan-2-one

1333-86-4 Carbon black

41556-26-7 bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate

· Proposition 65

Chemicals known to cause cancer:
 1330-20-7 xylene

1333-86-4 Carbon black

95-63-6 1,2,4-trimethylbenzene

98-82-8 cumene 100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 11)



(Contd. of page 9)

Page 10/12

USA




Page 11/12

Reviewed on 02/26/2013

Printing date 02/26/2013

Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06

Chemiculs KII	own to cause reproductive toxicity for males:	(Contd. of page 1
None of the ing	gredients is listed.	
Chemicals kn	own to cause developmental toxicity:	
None of the ing	gredients is listed.	
Cancerogenity	-	
	mental Protection Agency)	
67-64-1 ac		Ι
1330-20-7 xyl		I
98-82-8 cu		CBL
100-41-4 eth		D
	old Limit Value established by ACGIH)	
67-64-1 a		A^2
112-07-2 2	-butoxyethyl acetate	A
1330-20-7 x		A
14807-96-6 T	·	A
1333-86-4 C		A
100-41-4 et		A
	Vational Institute for Occupational Safety and Health)	
	ccupational Safety & Health Administration) gredients is listed.	
None of the ing GHS label ele	gredients is listed. <i>ments</i> The product is classified and labelled according to the Globally Harmoni <i>rams</i> GHS02, GHS08	zed System (GHS)
None of the ing GHS label elec Hazard pictog Signal word D Hazard-detern 1,6-HEXAME Solvent naphth Hazard statem	gredients is listed. ments The product is classified and labelled according to the Globally Harmoni rams GHS02, GHS08 Danger mining components of labelling: THYLENE DIISOCYANATE ha (petroleum), light arom. ments Tammable liquid and vapour.	ized System (GHS)
None of the ind GHS label elect Hazard pictog Signal word D Hazard-detern 1,6-HEXAME Solvent naphth Hazard statem H225 Highly f H315 Causes H319 Causes	gredients is listed. ments The product is classified and labelled according to the Globally Harmoni rams GHS02, GHS08 Danger nining components of labelling: THYLENE DIISOCYANATE ha (petroleum), light arom. ments Tammable liquid and vapour. skin irritation. serious eye irritation.	ized System (GHS)
None of the ind GHS label elect Hazard pictog Signal word D Hazard-detern 1,6-HEXAME Solvent naphth Hazard statern H225 Highly f H315 Causes H319 Causes H334 May cau	gredients is listed. ments The product is classified and labelled according to the Globally Harmoni trams GHS02, GHS08 Danger nining components of labelling: THYLENE DIISOCYANATE ha (petroleum), light arom. ments Tammable liquid and vapour. skin irritation. serious eye irritation. use allergy or asthma symptoms or breathing difficulties if inhaled.	ized System (GHS)
None of the ind GHS label elect Hazard pictog Signal word D Hazard-detern 1,6-HEXAME Solvent naphth Hazard statem H225 Highly f H315 Causes S H319 Causes S H334 May cau H317 May cau	gredients is listed. ments The product is classified and labelled according to the Globally Harmoni trams GHS02, GHS08 Danger nining components of labelling: THYLENE DIISOCYANATE tha (petroleum), light arom. tents lammable liquid and vapour. skin irritation. serious eye irritation. use allergy or asthma symptoms or breathing difficulties if inhaled. use an allergic skin reaction.	ized System (GHS)
None of the ind GHS label elect Hazard pictog Signal word D Hazard-detern 1,6-HEXAME Solvent naphth Hazard statem H225 Highly f H315 Causes S H319 Causes S H319 Causes S H314 May cau H317 May cau H340 May cau	gredients is listed. ments The product is classified and labelled according to the Globally Harmoni rams GHS02, GHS08 Danger mining components of labelling: THYLENE DIISOCYANATE tha (petroleum), light arom. ments Tammable liquid and vapour. skin irritation. serious eye irritation. use allergy or asthma symptoms or breathing difficulties if inhaled. use an allergic skin reaction. use genetic defects.	ized System (GHS)
None of the ina GHS label elect Hazard pictog Signal word D Hazard-detern 1,6-HEXAME Solvent naphth Hazard statem H225 Highly f H315 Causes S H319 Causes S H319 Causes S H317 May cau H317 May cau H340 May cau H350 May cau	gredients is listed. ments The product is classified and labelled according to the Globally Harmoni rams GHS02, GHS08 Danger mining components of labelling: THYLENE DIISOCYANATE tha (petroleum), light arom. ments Tammable liquid and vapour. skin irritation. serious eye irritation. use allergy or asthma symptoms or breathing difficulties if inhaled. use an allergic skin reaction. use genetic defects. use cancer.	ized System (GHS)
None of the ind GHS label elect Hazard pictog Signal word D Hazard-detern 1,6-HEXAME Solvent naphth Hazard statem H225 Highly f H315 Causes S H319 Causes S H319 Causes S H317 May cau H317 May cau H340 May cau H350 May cau Precautionary P210	gredients is listed. ments The product is classified and labelled according to the Globally Harmonic rams GHS02, GHS08 Danger mining components of labelling: THYLENE DIISOCYANATE ha (petroleum), light arom. ments Tammable liquid and vapour. skin irritation. serious eye irritation. use allergy or asthma symptoms or breathing difficulties if inhaled. use an allergic skin reaction. use genetic defects. use cancer. statements Keep away from heat/sparks/open flames/hot surfaces No smoking.	ized System (GHS)
None of the ing GHS label elect Hazard pictog Signal word D Hazard-detern 1,6-HEXAME Solvent naphth Hazard statem H225 Highly f H315 Causes S H319 Causes S H334 May cau H317 May cau H340 May cau H350 May cau Precautionary P210 P241	gredients is listed. ments The product is classified and labelled according to the Globally Harmonic rams GHS02, GHS08 Danger mining components of labelling: THYLENE DIISOCYANATE ha (petroleum), light arom. ments Tammable liquid and vapour. skin irritation. serious eye irritation. use allergy or asthma symptoms or breathing difficulties if inhaled. use an allergic skin reaction. use genetic defects. use cancer. b statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated of	
None of the ing GHS label elect Hazard pictog Signal word D Hazard-detern 1,6-HEXAME Solvent naphth Hazard statem H225 Highly f H315 Causes S H319 Causes S H319 Causes S H317 May cau H317 May cau H350 May cau H350 May cau Precautionary P210 P241 P303+P361+H P305+P351+H	gredients is listed. ments The product is classified and labelled according to the Globally Harmonic rams GHS02, GHS08 Danger mining components of labelling: THYLENE DIISOCYANATE ha (petroleum), light arom. ments lammable liquid and vapour. skin irritation. serious eye irritation. use allergy or asthma symptoms or breathing difficulties if inhaled. use an allergic skin reaction. use genetic defects. use cancer. p statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated of with water/shower. P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove present and easy to do. Continue rinsing.	clothing. Rinse sk
None of the ing GHS label elect Hazard pictog Signal word D Hazard-detern 1,6-HEXAME? Solvent naphth Hazard statem H225 Highly f H315 Causes S H319 Causes S H319 Causes S H334 May cau H350 May cau H350 May cau H350 May cau Precautionary P210 P241 P303+P361+1	gredients is listed. ments The product is classified and labelled according to the Globally Harmonic rams GHS02, GHS08 Danger mining components of labelling: THYLENE DIISOCYANATE tha (petroleum), light arom. ments Tammable liquid and vapour. skin irritation. serious eye irritation. use allergy or asthma symptoms or breathing difficulties if inhaled. use an allergic skin reaction. use genetic defects. use cancer. statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated of with water/shower. P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove	clothing. Rinse sk e contact lenses,





Reviewed on 02/26/2013

Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06

(Contd. of page 11)

· National regulations:

- · Information about limitation of use:
- Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environment protection department.
- · Contact: Steve Gaver

Abbreviations and acronyms: RiD: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organization ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association

- ACGIH: American Conference of Governmental Industrial Hygienists
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent