HAZARDOUS COMBUSTION

DOMINION SURE SEAL LTD. 6175 DANVILLE ROAD, MISSISSAUGA ONTARIO, CANADA L5T 2H7

PRODUCT: GRAVEL GUARD ROCKER GUARD COATING - BLACK SVG1 14.30Z/405G







Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER DOMINION SURE SEAL LTD. 6175 DANVILLE ROAD, MISSISSAUGA ONTARIO, CANADA L5T 2H7

PHONE: (905) 670-5411 CANUTEC EMERGENCY #: 1-613-996-6666 (24HR)

CHEMICAL FAMILY.

ORGANIC COATING.

MOLECULAR WEIGHT.

CHEMICAL FORMULA.

MIXTURE

MIXTURE TRADE NAMES & SYNONYMS...... NOT APPLICABLE PRODUCT USES..... COATING CAS #...... NOT APPLICABLE

Section 02: COMPOSITION/INFORMATION INGREDIENTS

Cotton CE. Comit Control of the Marie of the Cotton Cotton CE.					
Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route,Species	LC/50 Route,Species
ACETONE	10-45	750 ppm	67-64-1	>9750 mg/kg ORAL - RAT	>16,000 ppm (4 hr) INHAL - RAT
TOLUENE	10-30	50 ppm	108-88-3	5000 mg/kg ORAL - RAT	8000 ppm (4 hr) INHAL - RAT
CALCIUM CARBONATE	5-10	15 mg/m3	1317-65-3	NOT AVAILABLE	NOT AVAILABLE
CARBON BLACK	.1-1	3.5 mg/m3	1333-86-4	>10000 mg/kg ORAL - RAT	NOT AVAILABLE
ISOBUTANE	5 -10	1000 ppm	75-28-5	NOT APPLICABLE	142,500 ppm (4h) INHAL - RAT
PROPANE	10-30	1000 ppm	74-98-6	NOT APPLICABLE	NOT AVAILABLE

Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY: INHALATION..... ASPHYXIANT. MAY CAUSE IRRITATION. EYE CONTACT SKIN ADSORT HOW......SKIN CONTACT.....EFFECTS OF ACUTE EXPOSURE......EFFECTS OF CHRONIC EXPOSURE..... MAY CAUSE IRRITATION. DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES. SOLVENTS MAY CAUSE DEFATTING DERMATITIS EXPOSURE LIMIT OF MATERIAL..... SEE SECTION 2.

Section 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURE IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

Section 05: FIRE FIGHTING MEASURES

	AUTO IGNITION TEMPERATURE (°C)SPECIAL PROCEDURES	465 - 480. WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE
l		EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARTATUS SHOULD BE WORN IN A
l	FLAMMABILITY	FIRE INVOLVING THIS MATERIAL. EXTREMELY FLAMMABLE.
l	IF YES, UNDER WHICH CONDITIONS?	EXCESSIVE HEAT, SPARKS AND OPEN FLAME.
l	FLASH POINT (C), TAG CLOSED CUP	WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM.
l	UPPER FLAMMABLE LIMIT	
l	(% BY VOLUME) LOWER FLAMMABLE LIMIT	1
l	(% BY VOLUME)	I.
ı	EXPLOSION DATA	NOT ADDITIONAL F
l	SENSITIVITY TO STATIC DISCHARGE SENSITIVITY TO IMPACT	
- 1		

00007364	MATERIAL SAFETY DATA SHEET Page
	R GUARD COATING - BLACK SVG1 14.30Z/405G
	n 05: FIRE FIGHTING MEASURES
PRODUCTS AEROSOL FLAME PROJECTION	. HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
CLASSIFIED AS:	
Section 06	S: ACCIDENTAL RELEASE MEASURES
LEAK/SPILL	REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.
Section	n 07: HANDLING AND STORAGE
ENGINEERING CONTROLS	 KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES. VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS). STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C. NONE KNOWN.
Section 08: EXF	POSURE CONTROLS/PERSONAL PROTECTION
GLOVES/ TYPE	 IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED. SAFETY GLASSES. NOT NORMALLY REQUIRED.
Section 09:	PHYSICAL AND CHEMICAL PROPERTIES
PHYSICAL STATE	BLACK. AROMATIC ODOR. NOT AVAILABLE. 55 - 65. GREATER THAN 1.
(BY WEIGHT) SOLUBILITY IN WATER g/L (20°C) PH SPECIFIC GRAVITY (LIQUID) COEFFICIENT OF WATER\OIL DIST FREEZING POINT: (°C)	. NOT APPLICABLE. 0.95-0.99. NOT AVAILABLE.
Section	10: STABILITY AND REACTIVITY
HAZARDOUS PRODUCTS OF DECOMPOSITION	. NOT APPLICABLE STRONG OXIDIZING AGENTS NOT APPLICABLE.
Section 1	1: TOXICOLOGICAL INFORMATION
IRRITANCY OF MATERIALSENSITIZING CAPABILITY OF MATERIALCARCINOGENICITY OF MATERIAL	
Section 1	2: ECOLOGICAL CONSIDERATIONS
ENVIRONMENTAL	

00007364	MATERIAL SAFETY DATA SHEET Page
	GUARD COATING - BLACK SVG1 14.30Z/405G
	13: DISPOSAL CONSIDERATIONS
WASTE DISPOSAL	DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.
Section 14	1: TRANSPORTATION INFORMATION
D.O.T. CLASSIFICATIONT.D.G. CLASSIFICATION	CONSUMER COMMODITY, ORM-D. CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1).
Section	15: REGULATORY INFORMATION
CANADIAN REGULATIONS:	
WHMIS CLASSIFICATIONCNFC SECTION 3.3.5CEPA (Canadian Environmental Protection Act) U.S. REGULATIONS:	
HMIS RATING HEALTHHMIS RATING FLAMMABILITYHMIS RATING REACTIVITYHMIS RATING PERSONAL PROTECTIONNFPA CODE 30BSARA 313 INFORMATION:	3 SERIOUS HAZARD. 0 MINIMAL HAZARD. B.
TSCA (Toxic Substances Control Act)	THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986: WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. CAS #: CHEMICAL NAME: *108-88-3 TOLUENE ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING. COMPLIES WITH CARB MIR =1.40 FOR NON FLAT PAINTS AND 1.2 FOR FLAT PAINTS LESS THAN 40.
	on 16: OTHER INFORMATION
PREPARED BYPREPARATION DATE	THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY DOMINION SURE SEAL LTD. FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. DOMINION SURE SEAL ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS. TECHNICAL SERVICES August 8, 2012