



# TRIM #11 SILVER WHEELS AEROSOL (TRIMSLW/AL-US)

## Safety Data Sheet TRIMSLW/AL-US

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 04/12/2017

Revision date: 06/14/2017

Version: 2.0

## DRIVING SURFACE PERFECTION

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : TRIM #11 SILVER WHEELS AEROSOL (TRIMSLW/AL-US)  
Product group : Aerosol  
Other means of identification : UP0881

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

U-POL US Inc  
108 Commerce Way  
Stockertown PA 18083 - USA  
T 1-800-340-7824 - F 1-800-787-5150  
[technical.department@u-pol.com](mailto:technical.department@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC - 1-800-424-9300 ( UK +44 (0) 1933 230310 (07:30 - 17:00hrs UK time) )

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Aerosol 1 H222  
Skin Irrit. 2 H315  
Eye Irrit. 2 H319  
Carc. 2 H351  
STOT SE 3 H336  
STOT RE 2 H373

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H222 - Extremely flammable aerosol  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H351 - Suspected of causing cancer  
H373 - May cause damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation)

Precautionary statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P211 - Do not spray on an open flame or other ignition source  
P251 - Pressurized container: Do not pierce or burn, even after use  
P261 - Avoid breathing fume, spray, vapors  
P280 - Wear eye protection, protective clothing, protective gloves  
P302+P352 - If on skin: Wash with plenty of water  
P305 - IF IN EYES: Rinse first with plenty of water and if necessary take medical advice  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

# TRIM #11 SILVER WHEELS AEROSOL (TRIMSLW/AL-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Acetone	(CAS-No.) 67-64-1	23 - 43	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
xylene	(CAS-No.) 1330-20-7	5 - 23	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
4-methylpentan-2-one, isobutyl methyl ketone	(CAS-No.) 108-10-1	< 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319 STOT SE 3, H335
2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve	(CAS-No.) 111-76-2	< 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
ethylbenzene	(CAS-No.) 100-41-4	< 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
Solvent naphtha (petroleum), light arom.,		< 5	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurized container: may burst if heated.
Reactivity	: Extremely flammable aerosol. Pressurized container: may burst if heated.

# TRIM #11 SILVER WHEELS AEROSOL (TRIMSLW/AL-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapors, fume, spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain leaking substance. Collect spillage.  
Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe vapors, fume, spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.  
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
Storage temperature : < 25 °C  
Special rules on packaging : Keep only in original container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

TRIM #11 SILVER WHEELS AEROSOL (TRIMSLW/AL-US)		
ACGIH	Not applicable	
OSHA	Not applicable	
Acetone (67-64-1)		
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI
OSHA	OSHA PEL (TWA) (mg/m³)	2400 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
Solvent naphtha (petroleum), light arom.,		
ACGIH	Not applicable	

# TRIM #11 SILVER WHEELS AEROSOL (TRIMSLW/AL-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Solvent naphtha (petroleum), light arom.,

OSHA	Not applicable
------	----------------

### xylene (1330-20-7)

ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

### 4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)

ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	75 ppm
ACGIH	Remark (ACGIH)	URT irr; dizziness; headache
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	410 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

### ethylbenzene (100-41-4)

ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

### 2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve (111-76-2)

ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	50 ppm

## 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Personal protective equipment	: Gloves. Protective clothing. Safety glasses.



Materials for protective clothing	: Impermeable clothing.
Hand protection	: Protective gloves.
Eye protection	: Safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment.
Environmental exposure controls	: Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Color	: Metallic
Odor	: Odourless.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available

# TRIM #11 SILVER WHEELS AEROSOL (TRIMSLW/AL-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: $\approx -41$ °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: insoluble in water. soluble in most organic solvents.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurized container: may burst if heated.
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

MIR : 1.7

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurized container: may burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

xylene (1330-20-7)	
ATE US (dermal)	1100 mg/kg body weight
ATE US (dust, mist)	1.5 mg/l/4h
4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)	
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
ethylbenzene (100-41-4)	
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

# TRIM #11 SILVER WHEELS AEROSOL (TRIMSLW/AL-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve (111-76-2)

ATE US (oral)	500 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

### xylene (1330-20-7)

IARC group	3 - Not classifiable
------------	----------------------

### 4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

### ethylbenzene (100-41-4)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

### 2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve (111-76-2)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness.

Specific target organ toxicity – repeated exposure	: May cause damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation).
--	--

Aspiration hazard	: Not classified
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

### 12.2. Persistence and degradability

#### Solvent naphtha (petroleum), light arom.,

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

### 12.3. Bioaccumulative potential

#### Solvent naphtha (petroleum), light arom.,

Bioaccumulative potential	Not established.
---------------------------	------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on ozone layer	: No additional information available
Effect on the global warming	: No known effects from this product.

# TRIM #11 SILVER WHEELS AEROSOL (TRIMSLW/AL-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Regional legislation (waste) : Disposal must be done according to official regulations.
- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with DOT

- Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1
- UN-No.(DOT) : UN1950
- Proper Shipping Name (DOT) : Aerosols  
flammable, (each not exceeding 1 L capacity)
- Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
- Hazard labels (DOT) : 2.1 - Flammable gas



- DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 306
- DOT Packaging Non Bulk (49 CFR 173.xxx) : None
- DOT Packaging Bulk (49 CFR 173.xxx) : None
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
- DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### Additional information

- Other information : No supplementary information available.

#### ADR

- Transport document description : UN 1950 AEROSOLS, 2.1, (D)
- Class (ADR) : 2 - Gases
- Classification code (ADR) : 5F
- Hazard labels (ADR) : 2.1 - Flammable gases



- Tunnel restriction code (ADR) : D
- LQ : 1I
- Excepted quantities (ADR) : E0

#### Transport by sea

- UN-No. (IMDG) : 1950
- Proper Shipping Name (IMDG) : AEROSOLS
- Class (IMDG) : 2 - Gases

#### Air transport

- UN-No. (IATA) : 1950
- Proper Shipping Name (IATA) : Aerosols, flammable
- Class (IATA) : 2

# TRIM #11 SILVER WHEELS AEROSOL (TRIMSLW/AL-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

aluminium (Eckart)	CAS-No. 7429-90-5	< 5%
butan-1-ol, n-butanol	CAS-No. 71-36-3	< 5%
xylene	CAS-No. 1330-20-7	5 - 23%
isobutyl methyl ketone	CAS-No. 108-10-1	< 5%
ethylbenzene	CAS-No. 100-41-4	< 5%
toluene	CAS-No. 108-88-3	< 5%

#### Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ 5000 lb

#### Solvent naphtha (petroleum), light arom.,

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

#### xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ 100 lb

#### isobutyl methyl ketone (108-10-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ 5000 lb

#### ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ 1000 lb

#### 2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

No additional information available

##### EU-Regulations

No additional information available

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229

Skin Irrit. 2 H315

Eye Irrit. 2 H319

STOT SE 3 H336

Full text of hazard classes and H-statements : see section 16

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

##### 15.2.2. National regulations

#### isobutyl methyl ketone (108-10-1)

Listed on IARC (International Agency for Research on Cancer)

#### ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)

#### 15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm



# TRIM #11 SILVER WHEELS AEROSOL (TRIMSLW/AL-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

isobutyl methyl ketone (108-10-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	
ethylbenzene (100-41-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	54

## SECTION 16: Other information

Full text of H-phrases:

H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.

NFPA reactivity

: 3 - Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction but that require a strong initiating source or must be heated under confinement before initiation.



SDS US UPOL

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).