

Safety Data Sheet RCOL-US according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 11/15/2017 Revision date: 08/22/2018 Version: 1.1

SECTION 1: Identification			
1.1. Identification	• • •		
Product form	: Mixture		
Trade name	: RAPTOR COLOR		
UP Number		57, UP4858, UP4859, UP4860, UP4861, UP4862, UP486 67, UP4868, UP5031, UP5032, UP5033, UP5034, UP503 40	
1.2. Recommended use and restriction	ons on use		
Use of the substance/mixture	: Colouring agents		
Recommended use	: Coatings and paints, thinners, pain	it removers	
1.3. Supplier			
U-POL US Inc 108 Commerce Way, Stockertown PA 18083 - USA T 1-800-340-7824 - F 1-800-787-5150 technical.department@u-pol.com - www.u-po	l.com		
1.4. Emergency telephone number			
Emergency number	: CHEMTREC - 1-800-424-9300 ( L	JK +44 (0) 1933 230310 (07:30 - 17:00hrs UK time) )	
SECTION 2. Honord/a) identification			
SECTION 2: Hazard(s) identification			
2.1. Classification of the substance o	r mixture		
GHS-US classification			
Flammable liquids Category 3	Flammable liquid and vapo	זכ	
GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US) Precautionary statements (GHS-US)	smoking. Wear protective gloves, protective	liately all contaminated clothing. Rinse skin with	
<ul> <li>2.3. Other hazards which do not resule</li> <li>No additional information available</li> <li>2.4. Unknown acute toxicity (GHS US Not applicable</li> <li>SECTION 3: Composition/Information</li> <li>3.1. Substances</li> <li>Not applicable</li> </ul>	with local, regional, national and/or	azardous or special waste collection point, in accordance r international regulation	3
3.2. Mixtures			
Name	Product identifier	% GHS-US classification	
dodecylbenzene	(CAS-No.) 123-01-3	< 5 Asp. Tox. 1, H304 Aquatic Chronic 4, H413	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
POLYURETHANE	(CAS-No.) 68400-67-9	< 5	Skin Irrit. 2, H315

Full text of hazard classes and H-statements : see section 16

SECTION 4. First sidemoscore	
SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
4.2. Most important symptoms and e	ffects (acute and delayed)
No additional information available	
4.3. Immediate medical attention and	special treatment, if necessary
Treat symptomatically.	
SECTION 5: Fire-fighting measure	es de la companya de
5.1. Suitable (and unsuitable) extingu	
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
5.2. Specific hazards arising from the	: Flammable liquid and vapor.
Fire hazard	: Flammable liquid and vapor. : Flammable liquid and vapor.
Reactivity	
5.3. Special protective equipment and	
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 6: Accidental release m	easures
6.1. Personal precautions, protective	equipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information
	refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Avoid release to the environment.	
	amont and cleaning up
	Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public
Methods for cleaning up	waters.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	
For further information refer to section 13.	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Hygiene measures         7.2.       Conditions for safe storage, included	product.
	product.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection			
8.1.	Control parameters		
dodecy	ylbenzene (123-01-3)		
Not app	plicable		
POLYU	JRETHANE (68400-67-9)		
Not app	plicable		

### 8.2. Appropriate engineering controls

Appropriate engineering controls Environmental exposure controls

: Avoid release to the environment.

: Ensure good ventilation of the work station.

### 8.3. Individual protection measures/Personal protective equipment

### Hand protection:

Protective gloves

### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### **Respiratory protection:**

In case of insufficient ventilation, wear suitable respiratory equipment

## **SECTION 9: Physical and chemical properties**

	properties
Physical state : Liqui	id
Appearance : Liqui	id.
Color : Vario	ous
Odor : stror	ng
Odor threshold : No d	data available
pH : No d	data available
Melting point : Not a	applicable
Freezing point : No d	data available
Boiling point : No d	data available
Flash point : 38 °C	C
Relative evaporation rate (butyl acetate=1) : No d	data available
Flammability (solid, gas) : Not a	applicable.
Vapor pressure : No d	lata available
Relative vapor density at 20 °C : No d	lata available
Relative density : No d	lata available
Specific gravity / density : 1.3 g	g/cm³
Solubility : No d	lata available
Log Pow : No d	lata available
Auto-ignition temperature : No d	lata available
Decomposition temperature : No d	lata available
Viscosity, kinematic : No d	data available
Viscosity, dynamic : No d	lata available
Explosion limits : No d	lata available
Explosive properties : No d	lata available
Oxidizing properties : No d	lata available

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to					
9.2.	Other information				
VOC con	itent	: 330 g/l			
SECTIO	ON 10: Stability and read	tivity			
10.1.	Reactivity				
	ble liquid and vapor.				
10.2.	Chemical stability				
Stable ur	nder normal conditions.				
10.3.	10.3. Possibility of hazardous reactions				
No dange	erous reactions known under no	mal conditions of use.			
10.4.	10.4. Conditions to avoid				
Avoid co	Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.				
10.5.	10.5. Incompatible materials				
No additi	ional information available				
10.6.	10.6. Hazardous decomposition products				
	Under normal conditions of storage and use, hazardous decomposition products should not be produced.				
	ON 11: Toxicological inf				
<u>3ECTR</u>					
	Information on toxicological				
	kicity (oral)	: Not classified			
	kicity (dermal)	: Not classified			
Acute tox	kicity (inhalation)	: Not classified			
Skin corr	osion/irritation	: Not classified			
Serious e	eye damage/irritation	: Not classified			
Respirato	ory or skin sensitization	: Not classified			
Germ cel	Il mutagenicity	: Not classified			

Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated	: Not classified
exposure	
Appiration hazard	. Not close if ad
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available

<b>SECTION 12: Ecological informa</b>	ation
12.1. Toxicity	
Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.	
dodecylbenzene (123-01-3)	
LC50 fish 1	796 mg/l (Leuciscus idus)
12.2. Persistence and degradability dodecylbenzene (123-01-3)	
Persistence and degradability	Readily biodegradable in water.
12.3. Bioaccumulative potential	
dodecylbenzene (123-01-3)	
BCF fish 1	35 (Pisces)
Bor han i	35 (T 13003)
BCF fish 2	1250 (Lepomis macrochirus)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

dodecylbenzene (123-01-3)		
Bioaco	cumulative potential	Potential for bioaccumulation (500 $\leq$ BCF $\leq$ 5000).
12.4.	Mobility in soil	
No addit	tional information available	
12.5.	Other adverse effects	
12.5.	Other adverse effects	

No additional information available

<b>SECTION 13: Disposal consideratio</b>	ns
13.1. Disposal methods	
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapors may accumulate in the container.
<b>SECTION 14: Transport information</b>	
Department of Transportation (DOT) In accordance with DOT	
Transport document description	: UN1263 Paint, 3, III

I ransport document descriptio UN-No.(DOT) Proper Shipping Name (DOT) Class (DOT) Packing group (DOT) Hazard labels (DOT)

- : UN1263
- : Paint
- : 3 Class 3 Flammable and combustible liquid 49 CFR 173.120
- : III Minor Danger
- : 3 Flammable liquid



: 173

: 242

DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)

- DOT Special Provisions (49 CFR 172.102)
- 367 For the purposes of documentation and package marking: a. The proper shipping name "Paint related material" may be used for consignments of packages containing "Paint" and "Paint related material" in the same package; b. The proper shipping name "Paint related material, corrosive, flammable" may be used for consignments of packages containing "Paint, corrosive, flammable" and "Paint related material, corrosive, flammable" and "Paint related material, corrosive, flammable" and "Paint related material, corrosive, flammable" in the same package; c. The proper shipping name "Paint related material, flammable, corrosive" may be used for consignments of packages containing "Paint, flammable, corrosive" and "Paint related material, flammable, corrosive, flammable, corrosive, flammable, corrosive, flammable, coro

flammable, corrosive and Paint related material, flammable, corrosive, and the proper shipping name "Printing ink related material, ink

B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

## Safety Data Sheet

coording to Federal Register / Vol. 77, No. 58 / Monday,	
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.
Fransportation of Dangerous Goods	
Fransport document description	: UN1263 PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler an liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass), 3, III
UN-No. (TDG)	: UN1263
Proper Shipping Name (Transportation of Dangerous Goods)	: PAINT
TDG Primary Hazard Classes	: 3 - Class 3 - Flammable Liquids
Packing group	: III - Minor Danger
TDG Special Provisions	<ul> <li>59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (k dry mass),142 - The following shipping names may be used to meet the requirements of Part (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment: (a)"PAINT RELATED MATERIAL may be used for a means of containment containing both paint related material;</li> <li>(b)"PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for a means of containment containing both paint, related material, corrosive flammable; (c)"PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d)"PRINTING INK RELATED MATERIAL" may be used for a mean of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d)"PRINTING INK RELATED MATERIAL" may be used for a mean of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d)"PRINTING INK RELATED MATERIAL" may be used for a mean of containment containing both printing ink and printing ink related material. SOR/2014-306</li> </ul>
Explosive Limit and Limited Quantity Index	: 5L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 60 L
Transport by sea	
Transport document description (IMDG)	: UN 1263 PAINT, 3, III
UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
imited quantities (IMDG)	: 5L
Air transport	
	: UN 1263 Paint, 3, III
Transport document description (IATA)	: 1263
	. 1205
Transport document description (IATA) UN-No. (IATA) Proper Shipping Name (IATA)	: Paint
UN-No. (IATA)	

## SECTION 15: Regulatory information 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

dodecylbenzene	CAS-No. 123-01-3	< 5%
POLYURETHANE	CAS-No. 68400-67-9	< 5%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 15.2. International regulations

CANADA No additional information available

**EU-Regulations** No additional information available

National regulations No additional information available

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
dodecylbenzene(123-01-3)	
POLYURETHANE(68400-67-9)	

### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date

: 08/22/2018

#### Full text of H-phrases:

[	H304	May be fatal if swallowed and enters airways
	H315	Causes skin irritation
	H413	May cause long lasting harmful effects to aquatic life

SDS US GHS (GHS HazCom2012) - U-POL

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.